

Index

An excerpt from the *Dimension Stone Design Manual 2022*
(April 2022)



**Produced and Published by the
Natural Stone Institute
380 East Lorain St. Oberlin, Ohio 44074
Telephone: 440-250-9222
Fax: 440-774-9222
www.naturalstoneinstitute.org**

Disclaimer: This manual contains general guidelines. The Natural Stone Institute and its Member companies are not responsible for any use or misuse that causes damage of any kind, including loss of rights, material, and personal injury alleged to be caused directly or indirectly by the information contained in this manual.

© 2022 Natural Stone Institute
© 2016 Marble Institute of America (Chapter 21, 22, Glossary, Appendix and Index)
© 2011 Marble Institute of America (Chapter 17, Glossary and Index)
© 2010 Marble Institute of America (Chapters 13, 14, 15, and Index)
© 2007 Marble Institute of America (All other Chapters)

All rights reserved. No part of this document may be reproduced or transmitted in any form or by means electronic or mechanical, including photocopy, recording, or by an information storage and retrieval system, without written permission from the Natural Stone Institute.

Index

Note: Page numbers in *italics* refer to figures. Page numbers that refer to footnotes include the number of footnote (for example, 10-7 n2).

A

- abate, defined, 23-1
- abrasion index, 4-8
- abrasion resistance
 - flooring, 4-8
 - foot traffic, 13-4
 - granite, 5-11
 - horizontal applications, 13-4
 - limestone, 6-12, 6-13
 - marble and onyx, 7-17 to 7-18
 - quartz-based stone, 8-12
 - serpentine, 9-13
 - serpentine, 9-14
 - slate, 10-11
 - thin-stone pavers, 4-3
 - travertine, 12-12
 - travertine, 12-13
- abrasion resistance index, 4-8
- abrasive finish
 - defined, 23-1
 - exterior cubic stone coping and walls, 18-1
 - limestone, 6-10
 - marble and onyx, 7-3, 7-14
 - marble and onyx
- abrasive hardness
 - defined, 23-1
 - foot traffic, 14-1
 - pavers, 14-1
 - stair treads, 14-13
- abrasives
 - abrasive bonds, 21-31 to 21-32
 - abrasive pads
 - defined, 21-31
 - fiber pads, 21-31
 - synthetic fiber pads, 21-31
 - dot pads, 21-31
 - bricks, 21-29 to 21-30
 - copper bond, 21-33 to 21-34
 - diamond, 21-29
 - diamond abrasive pads, 21-33
 - electroplated bonds, 21-34
 - frankfurt
 - defined, 21-30
 - magnesite bond, 21-30
 - synthetic bond, 21-30
 - hard synthetic bond, 21-30
 - polishing and cleaning brick, 21-30
 - glazing over, 21-48
 - plugs, 21-30
 - resin bond abrasives, 21-32
 - rigid resin diamond abrasives, 21-47
 - silicon carbide, 21-29
 - sintered bond, 21-33
 - turbo-style resin diamond abrasives, 21-47
 - uses for, 21-29
 - vacuum brazed diamond abrasives, 21-34
 - water supply, 21-48
 - water use, 21-48
- absorption of stone
 - defined, 23-1
 - exterior application, 3-4
 - granite, 5-11
 - limestone, 6-12
 - marble and onyx, 7-17
 - quartz-based stone, 8-11
 - serpentine, 9-13
 - slate, 10-11
 - travertine, 12-12
- absorption rate, 4-1
- abutment, defined, 23-1
- accelerators, defined, 23-1
- accelerators, staining and, 21-40
- access routes, damage prevention, 21-25
- accessories, *14-D.23 to 14-D.25*
- acid etched finish, defined, 21-6
- acid wash, defined, 23-1
- acid washed finish, 3-2
 - defined, 21-6
- acids, 21-3 to 21-4
 - cleaning with, 21-84
- acrylic-epoxy, properties, 21-49
- acrylic resin, 17-7, 17-10
- acrylics, properties, 21-49
- ADA requirements, 21-75
- adhered fiberglass netting reinforcement, 16-10
- adhered, defined, 23-1
- adhesive
 - acrylic-epoxy, properties, 21-49
 - acrylics, 21-40 to 21-41
 - properties, 21-49
 - bond strength, 21-20
 - consistency, 21-45
 - countertops, 17-6, 17-7, 17-13
 - coverage, 21-19 to 21-20
 - cyanoacrylate (CA) glues, 21-41 to 21-42
 - properties, 21-49
 - epoxy, 21-41
 - properties, 21-49
 - for repairs, 21-39
 - consistency, 21-45
 - general notes, 21-42
 - granite, 5-3
 - green marble, 13-18
 - hybrids, 21-42
 - identification, 21-19
 - maintenance, 21-76
 - marble and onyx, 7-3
 - outdoor kitchens, 17-13
 - penetrating adhesives, 21-45
 - poly-epoxy, properties, 21-49
 - polyester, 21-40
 - properties, 21-49
 - selection, 21-19
 - serpentine, 9-4, 9-8, 13-18
 - urethane, 21-41
 - properties, 21-49
- adhesive repairs, 21-8
- admixture, defined, 23-1
- adoquin, defined, 23-1
- aesthetics, 3-1 to 3-2
- agate, 8-7, 8-9
 - defined, 23-1
- agglomerated stone, defined, 23-1
- aggregate, defined, 23-1
- alabaster
 - composition of, 1-6
 - defined, 23-1
- albite, 9-11
- alignment, tolerances, 22-7 to 22-8
- alkaline, defined, 23-1
- alkalinity sensitivity, 13-18
- alkalis, cleaning with, 21-84
- allowable capacity, defined, 23-1
- allowable repair of countertops, 17-11 to 17-12
- aluminum oxide, polishing powders, 21-35
- ambient temperature, defined, 23-1
- American Institute of Architects (AIA), vi
- American National Standards Institute (ANSI), 2-3
- American Society of Testing and Materials (ASTM), sustainability, vii to viii
- amphibole, 11-5
- anchorage
 - defined, 23-2
 - granite, 5-7
 - interior cladding, 14-14 to 14-15
 - limestone, 6-6 to 6-7
 - marble and onyx, 7-7
 - quartz-based stone, 8-5 to 8-6
 - serpentine, 9-7
 - slate, 10-6
 - thermal isolator, 14-10
 - travertine, 12-6
- anchors, *14-D.23 to 14-D.25*
 - aluminum, 5-3

- back, 14-5
 - defined, 23-3
 - with clips, *14-D.5*
 - bent plate, 14-4
 - column, free-standing, *14-D.12*
 - cramp anchor, defined, 23-8
 - defined, 23-2
 - dowel, 14-4
 - expansion, *14-D.1, 14-D.4*
 - exterior stone veneer, *14-D.1* to *14-D.7*
 - goose neck, *14-D.25*
 - granite, 5-3
 - hairpin precast, *14-D.25*
 - hairpin spring
 - slate panels, 10-5
 - quartz-based stone panels, 8-5
 - interior stone veneer, *14-D.8*
 - lace, *14-D.25*
 - limestone, 6-4
 - masonry bed, 14-5
 - mechanical anchors, 21-18
 - mechanical systems, 14-14 to 14-15
 - nonferrous, 6-4
 - pin, 14-4
 - plug, *14-D.24*
 - serpentine, 9-4
 - shelf, 14-4
 - showers, residential, 16-8
 - split-tail anchor, exterior stone veneer, *14-D.2, 14-D.3*
 - stainless steel, 5-3, 6-4, 12-3
 - strap, 14-4
 - slate, 10-5
 - stair treads, *13-D.7* to *13-D.8*
 - T-31 back, *14-D.24*
 - thin stone, 14-5
 - tolerances, 22-6
 - travertine, 12-3
 - vertical surfaces, 14-4 to 14-6, *14-D.23* to *14-D.25*
 - wet areas, 16-1
 - wire loop anchor, *14-D.21*
 - anchors, wire, 14-5, *14-D.25*
 - copper, 7-3 to 7-4, 9-4
 - interior cladding, *14-D.10*
 - non-ferrous, 8-3, 10-3, 10-5
 - quartz-based stone, 8-3
 - serpentine, 9-4
 - slate, 10-3, 10-5
 - installation, 10-5
 - stainless steel, 7-3 to 7-4, 9-4
 - stair treads, *13-D.8*
 - tie back, *14-D.17*
 - Andesite, 1-3
 - angle of repose, defined, 23-2
 - angular grain (sand), 1-5
 - anisotropic, defined, 23-2
 - anorthosite, 5-9
 - defined, 23-2
 - ANSI (American National Standards Institute), 2-3, 2-6, 23-2
 - antiqued finish, 6-10
 - countertops, 17-2
 - defined, 23-2
 - antiquing brushes, 21-37
 - apatite, hardness, 21-2
 - apex stone, defined, 23-2
 - appearance, 3-1 to 3-2
 - aprons, for stone tile countertops, 17-9
 - defined, 23-2
 - aragonite, 6-9
 - arch, defined, 23-2
 - architrave, *23-7, 23-8, 23-10, 23-12*
 - defined, 23-2
 - area, conversion ratios, 24-2
 - argillite, defined, 23-2
 - arkose, defined, 23-2
 - arris, 17-6, 17-12
 - defined, 23-2
 - stone edges, 13-6
 - artificial stone, defined, 23-2
 - artwork and antiques, 21-25
 - asbestos, 9-3, 9-9 to 9-10
 - ashlar
 - coursed ashlar, 23-2
 - defined, 23-2
 - random ashlar, 23-2
 - stacked ashlar, 23-2
 - ASI (Allied Stone Industries), defined, 23-2
 - ASTM (American Society of Testing and Materials), sustainability, vii to viii
 - ASTM Classification Index, 24-4
 - ASTM Committee on Stone (C-18), 4-2
 - ASTM International, 2-2 to 2-3, 4-2
 - defined, 23-2
 - ASTM standards, 4-2
 - development of, 2-2 to 2-3
 - granite, 5-1 to 5-2
 - horizontal applications, 4-3
 - limestone, 6-1
 - marble, 7-1
 - material specifications, 2-4
 - onyx, 7-1
 - other application standards, 2-5 to 2-6
 - quartz-based stone, 8-1
 - serpentine, 9-1
 - slate, 10-1
 - soapstone, 11-1
 - test standards, 2-4 to 2-5
 - travertine, 12-1
 - ASTM tests, 3-6, 4-1, 4-2
 - augite, 11-5
 - axed finish, marble and onyx, 7-14
 - axed work (*British*), defined, 23-2
- ## B
- back anchor
 - defined, 23-3
 - soffits, *14-D.18*
 - T-31, *14-D.24*
 - undercut, *14-D.24*
 - back buttering
 - interior cladding, 14-15
 - stone tile countertops, 17-9
 - back-checking granite, 5-4
 - limestone, 6-5
 - marble and onyx, 7-4
 - quartz-based stone, 8-4
 - serpentine, 9-4
 - slate, 10-4
 - travertine, 12-4
 - backer rod, defined, 23-3
 - backing materials, portland cement mortar, 14-6
 - backing rods, *13-D.1, 13-10* to 13-11, *14-D.9*
 - back-parging, defined, 23-3
 - backsplashes, 17-5, *17-D.12*
 - defined, 23-3
 - back-up structure, defined, 23-3
 - backup walls, 18-1
 - bacteria, 21-84
 - granite, 5-14
 - baluster, defined, 23-3
 - balustrade, defined, 23-3
 - band course (string course), defined, 23-26
 - banker, defined, 23-3
 - basalt, defined, 23-3
 - basaltic lava, 1-3, 5-9
 - base
 - cove base, defined, 23-8
 - defined, 23-3
 - base design, furniture and tops, 19-1
 - base molding, *23-7, 23-9, 23-18, 23-19*
 - baseboards, damage prevention, 21-25
 - basic, defined, 23-3
 - batted work (*British*), defined, 23-3
 - battered splay, free-standing

column, *14-D.14*
bearing check, defined, 23-3
bed, defined, 23-3
bed joint, defined, 23-3
bed width
 granite, 5-4, 5-8
 marble and onyx, 7-4
 quartz-based stone, 8-3
 serpentine, 9-4
 slate, 10-3
 travertine, 12-4
bedding plane, defined, 23-3
bedrock, defined, 23-4
beds
 granite, 5-4
 limestone, 6-4
 marble and onyx, 7-4
 quartz-based stone, 8-3
 serpentine, 9-4
 slate, 10-3
 travertine, 12-4
belt course, defined, 23-4
bench, defined, 23-4
bending strength, 4-6, 5-12
bent rod, *14-D.24*
beveled block joint, *14-D.16*
bevels, furniture and tops, 19-1
biotite, 5-8, 5-9, 17-12
biscuits, countertop repair, 21-46
black granite, 5-9
 defined, 23-4
blade dressing, defined, 23-4
bleed, defined, 23-4
blend pattern, *7-D.2*
blending, defined, 23-4
blind connections, exterior stone
 vener, *14-D.5*
bluestone, defined, 23-4
bollard, defined, 23-4
bond, defined, 23-4
bonding
 cubic sills, 18-3
 exterior cubic stone coping and
 walls, 18-1
 window stools, 18-3
bond stones, 18-1
bond strength, 21-20
book match pattern, *7-D.3, 19-D.2*
 defined, 23-4
border stone, defined, 23-4
boss, defined, 23-4
boulder conglomerate, 1-5
boulder, defined, 23-4
boulders, clast size, 1-5
bowing
 See also hysteresis
 defined, 23-4
bracket detail, interior cladding, *14-*

D.15
breccia, defined, 23-4 to 23-5
brecciated marble, 23-5
bricks, as abrasives, 21-29 to 21-30
bridge crane, defined, 23-5
bridge polisher, defined, 23-5
bridge saw, defined, 23-5
broach, defined, 23-5
brownstone
 composition of, 1-6
 defined, 23-5
brucite, 9-9, 9-11
brushed finish
 countertops, 17-2
 defined, 23-5
 granite, 21-62
 MTL, 21-58
brushes
 antiquing brushes, 21-37
 carbide bristle brushes, 21-37
 diamond wire brushes, 21-37
 rubber bristle brushes, 21-37
BSI (Building Stone Institute),
 defined, 23-5
budgetary concerns, 21-72
bugged finish, defined, 23-5
building cleaning, 21-83 to 21-84
building movement
 consultants, 21-26
 cracks, 21-22
buildings
 occupants, 21-25
 structural problems, 21-26
building stone, defined, 23-5
Building Stone Institute (BSI),
 defined, 23-5
bullnose edge, *17-D.16, 19-D.3*
 corner joinery, *17-D.3*
 tolerances, *22-D-App B*
bullnose, defined, 23-5
bush hammering, defined, 23-5
bush-hammered finish, 3-2
 granite, 5-7, 21-62
 limestone, 6-10
 marble and onyx, 7-14
 MTL, 21-58
 slate, 10-9
 weakening of stone, 6-10, 8-10
business schedules, 21-26
butt joint, *14-D.9, 14-D.16*
 defined, 23-5
buttering, defined, 23-5

C

C-18 (ASTM Committee on
Stone), 4-2
CA glue (cyanoacrylate), 21-40

cabinet components, 17-4
cabinet measurements, 17-3
calcarenite, defined, 23-5
calcareous, defined, 23-5
calcareous stones
 acid attack, 21-3
 behavioral groups, consistent,
 21-11
 behavioral groups, variegated,
 21-14
 defined, 21-2
 sealers, 21-69 to 21-70
calcite, 1-6, 9-10
 abrasion resistance, 24-4
 absorption of stone, 24-4
 acid reaction, 7-11
 anisotropy, 7-11 to 7-12
 as cementing material, 1-6
 chemical properties, 7-10 to 7-
 11
 cleaning and maintenance, 21-
 79
 cleavage, 7-11
 color, 7-11
 composition of, 7-11
 compressive strength, 24-4
 crystals, 7-10 to 7-11
 defined, 23-6
 density, 24-4
 dolomite vs., 6-9
 flexural strength, 24-4
 hardness, 6-9, 21-2
 Iceland Spar, 7-11
 in limestone, 6-9
 in marble, 7-9
 maintenance, 21-76
 modulus of rupture, 24-4
 optical character, 7-11
 physical properties, 7-10 to 7-
 11, 24-4
 thermal hysteresis, 7-12 to 7-13
 water absorption, 24-4
calcite limestone, defined, 23-6
calcite marble, defined, 23-6
calcite streaks, defined, 23-6
calcium carbonate, weather
 resistance of, 10-13
calibration, defined, 23-6
canopy, defined, 23-6
cantera, defined, 23-6
cantilevers, 17-4
 defined, 23-6
cap (or capital) , 23-7, 23-8, 23-9,
23-10, 23-12, 23-18, 23-19
 defined, 23-6
carbide bristle brushes, 21-37
carbonates, as cementing material,
 1-6

- carbonatites, 6-8 n2
- carbonic acid, defined, 23-6
- carve, defined, 23-6
- carving, 13-2
 - granite, 5-4
 - limestone, 6-5
 - marble and onyx, 7-5
- models
 - granite, 5-4
 - limestone, 6-5
 - marble and onyx, 7-5
 - serpentine, 9-5
 - travertine, 12-5
- serpentine, 9-5
- travertine, 12-5
- cast-iron sinks, 17-3
- caulk, defined, 23-6
- caulking, slate, 10-6
- caulking
 - granite, 5-6
 - limestone, 6-7
 - marble and onyx, 7-7
 - quartz-based stone, 8-6
 - serpentine, 9-8
 - soapstone, 11-3 to 11-4
 - travertine, 12-7
- cautions, vertical surfaces, 14-16 to 14-17
- cavities, 14-3 to 14-4
- cavity vent, defined, 23-6
- cavity wall, defined, 23-6
- ceiling channel for toilet partitions, 16-3
- ceiling-hung, toilet partitions, *16-D.1*
- ceilings in steam rooms and showers, 16-8, 16-12
- cement backer board, interior stone veneer, *14-D.8*
- cement butter (neat cement), defined, 23-17
- cement putty (neat cement), defined, 23-17
- cementing minerals, 1-5 to 1-6
- cementitious backer units, 13-11, *16-D.8, 16-D.10*
 - horizontal applications, 13-11
 - mold and mildew, 16-2
 - thin-bed mortar, 13-16
- CEN standards, 2-6
- centimeters to inches, 24-1
- chamfer, defined, 23-6
- chamfer edge, 13-6, *17-D.16, 19-D.3*
 - tolerances, *22-D-App B*
- chat sawn finish, defined, 23-6
- chemical analysis, 4-1
- chemical cleaning, 21-84
- chemical precipitates, 1-1 to 1-2
- chemical reactivity of soapstone, 11-5
- chemical resistance, 21-3 to 21-4
- chemical sedimentary stone, 1-1 to 1-2, 1-6
- chemical sensitivity, sealers, 21-69
- chert, 1-6, 8-7, 8-9
 - defined, 23-6
- chips, 21-23
 - countertops, 17-12
 - repairs, 21-44
- chiseled edge, *17-D.16, 19-D.3*
 - defined, 23-6
- chlorite, 7-9, 9-11
- chrysotile (asbestos), 9-10
- cladding, defined, 23-6
- clast, defined, 23-6
- clast sizes, 1-4 to 1-5
- clastic sedimentary stone, 1-4 to 1-5
- clay
 - clast size, 1-5
 - coloring in limestone, 6-9
 - defined, 10-7 n2
- clay balls, travertine, 12-9
- clay minerals as cementing material, 1-6
- cleaners, 21-36 to 21-37
 - acidic cleaners, 21-37
 - alkaline cleaners, 21-36
 - neutral cleaners, 21-36
- cleaning
 - building cleaning
 - specifications, 21-83 to 21-84
 - commercial cleaning and sealing, 21-78 to 21-79, 21-87
 - countertops, 17-13
 - granite, 5-7
 - granite countertops, 21-64
 - limestone, 6-7
 - marble and onyx, 7-7
 - quartz-based stone, 8-6
 - residential cleaning, 21-77 to 21-78
 - serpentine, 9-8
 - slate, 10-6
 - soapstone, 11-4
 - travertine, 12-7
- cleaning tools, 21-43
- cleavage, 10-8
 - crystalline quartz, 8-7
 - defined, 23-7
- cleavage membranes, 13-7, 14-3
- cleavage plane, defined, 23-7
- cleft finish, defined, 21-6, 23-7
- Clinton, Bill, vi
- closed-cell ethafoam rope backer rod, 5-6
 - limestone, 6-7
 - quartz-based stone, 8-6
 - serpentine, 9-7
 - slate, 10-6
- closer (*British*), defined, 23-7
- CNC machine, defined, 23-7
- coatings, 21-67 to 21-68
 - detailing, 21-52
 - poulticing, 21-52
 - removal of, 21-51
 - solvent-based coatings, 21-52
 - water-based coatings, 21-51 to 21-52
- cobble conglomerate, 1-5
- cobbles, clast size, 1-5
- cobblestone, defined, 23-7
- Code of Federal Regulations, Title 21, 2-4
- coefficient of friction (COF), 4-9
 - pavers, 13-5
- coefficient of thermal expansion
 - granite, 5-11
 - limestone, 6-12
 - marble and onyx, 7-17
 - precast concrete panels, 20-1
 - serpentine, 9-15
 - slate, 10-11
 - stone veneer panels, 20-1
- cold applied membrane, defined, 16-2
- cold weather and installation of limestone, 6-6
- colonnade, defined, 23-7
- color, 13-3
 - precast concrete panels, 20-1
 - resin-impregnated slabs, 17-10
 - stone veneer panels, 20-1
- color and veining
 - crystalline quartz, 8-8
 - granite, 5-9
 - limestone, 6-10
 - marble and onyx, 7-13
 - quartz-based stone, 8-9
 - serpentine, 9-11 to 9-12
 - slate, 10-8
 - translucence, 7-21
 - travertine, 12-10
- color enhancer/sealer, defined, 23-7
- color matching, 21-46
- colored waxes, 21-7
- colors and tints, in adhesives and patching materials, 21-39 to 21-40, 21-42 to 21-43
- column, defined, 23-7
- commercial center environments, diagnostic considerations, 21-24
- commercial restoration

- additional resources, 21-121 to 21-122
- labor restrictions, 21-87
- levels of pedestrian traffic, 21-85
- multi-component surfaces, 21-86
- payment, 21-88
- performance expectations, 21-88
- revolving doors, 21-86
- rules and regulations, 21-85
- size of project, 21-85
- staircases, 21-86
- stone trim, 21-86
- vertical surfaces, 21-86
- work approval, 21-88
- common joint for countertops, *17-D.3*
- compressive loads, 4-5
- compressive strength
 - defined (ASTM C170), 23-7
 - granite, 5-11 to 5-12
 - limestone, 6-12
 - marble and onyx, 7-17
 - measurement, 4-5 to 4-6
 - precast concrete panels, 20-1
 - quartz-based stone, 8-11
 - serpentine, 9-13
 - slate, 10-10
 - stone veneer panels, 20-1
 - travertine, 12-12
- concrete flooring, cast in place, 13-5
- concrete subsurface, *13-D.3*, *13-D.4*, 14-8 to 14-9
 - mortar bed bonded to, 13-11 to 13-12
- concrete walls, exterior stone veneer, *14-D.1*, *14-D.5*
- concrete/CMU backup, 14-14
- conference table, *19-D.1*, *19-D.2*
- conglomerate, defined, 23-7
- construction (cold) joint, defined, 23-7
- continental stone, 1-2 to 1-3
- contraction joint, defined, 23-11
- contractor, stone, defined, 23-7
- contracts
 - for countertops, 17-3
 - suggested, xii to xiii
- control joints, defined, 21-19, 23-7
- conversion ratios, 24-2
- conversion tables, 24-1 to 24-2
- conveyor, defined, 23-7
- coping
 - defined, 23-7
 - flush face stone, *18-D.1*
 - projected stone, *18-D.1*
 - sloped stone, *18-D.1*
- copper wire anchors
 - marble, 7-3 to 7-4
 - onyx, 7-3 to 7-4
 - serpentine, 9-4
- coquina, defined, 23-7
- corbel, defined, 23-7
- core bit, defined, 23-8
- core, defined, 23-7
- core (Earth), 1-2
- core sampling, defined, 23-8
- corner block joint, *14-D.16*
- corner cove joint, *14-D.16*
- corner embellishments of countertops, 17-4
- corners, standard, for exterior stone veneer, *14-D.9*
- cornerstone, defined, 23-8
- cornice, *23-7*, *23-10*, *23-12*
 - defined, 23-8
- corrosion-resistant metals
 - cubic sills, 18-3
 - window stools, 18-3
- corundum, hardness, 21-2
- cost of stone, 3-7 to 3-8
 - maintenance, 3-8
- countertops, 3-5
 - adhesive, 17-6, 17-7, 17-13
 - allowable repairs, 17-11 to 17-12
 - arris, 17-6
 - backsplashes, 17-5
 - bullnose edge, *17-D.3*
 - cabinet requirements, 17-3
 - cantilevers, 17-4
 - cleaning, 17-13
 - common joint, *17-D.3*
 - contracts, 17-3
 - corbel supports, *17-D.1* to *17-D.2*, *17-D.14*, *17-D.15*
 - corner embellishments, 17-4
 - corner joinery, *17-D.3*
 - cracks, 17-11 to 17-12
 - crating, 17-5
 - customer communication, 17-2 to 17-3, 17-13
 - cutouts, 17-5
 - details, *17-D.4* to *17-D.10*, *17-D.14* to *17-D.15*
 - documentation of
 - communication, 17-2 to 17-3
 - doors, *17-D.7*
 - drop-in sink styles, *17-D.10*
 - dry assembly, 17-5
 - edge profiles, 17-4, *17-D.13*, *17-D.16*
 - finishing, 17-5
 - elastomeric sealant, 17-7, 17-9
 - epoxy resin, 17-7, 17-9
 - exposed edges, 17-6
 - fabrication, 17-5
 - fiberglass mesh backing, adhesive, 17-11
 - field measurements, 17-3 to 17-4
 - final positioning, 17-3, 17-6
 - finishes, 17-2
 - fissures, 17-11
 - flush subtops, *17-D.6*
 - granite, 3-5 to 3-6, 17-1
 - grout, 17-9
 - impregnators (penetrating sealers), 17-12 to 17-13
 - installation, 17-5 to 17-6
 - stone tile, 17-9
 - joinery layout, 17-4
 - joint filling, 17-6
 - joint width, 17-6
 - joints at sink, *17-D.1*, *17-D.4*
 - joints away from sink, *17-D.2*
 - kitchen layouts, *17-D.1* to *17-D.2*
 - layout, 17-5
 - limestone, 17-2
 - liner blocks, 17-11
 - lippage, 17-6, *17-7*
 - maintenance, 17-12 to 17-13
 - marble
 - miter joint, *17-D.3*
 - no joints at sink, *17-D.5*
 - no subtops, *17-D.6*
 - onyx, 17-1
 - outdoor kitchens
 - overhangs, *17-D.7* to *17-D.8*, *17-D.15*
 - pitting, 17-12
 - polishing, 21-62
 - polyester resin, 17-9
 - protective transport, 17-5
 - radius edges, *17-D.8*
 - recessed hardware for doors, *17-D.7*
 - reinforcement techniques, 17-11
 - repairing damaged stone, 17-11 to 17-12
 - resin-impregnated slabs, 17-11
 - resin-treated, 3-6
 - rodding, 17-11, *17-D.1* to *17-D.2*, *17-D.5*
 - safe work practices, 17-5
 - sawing, 17-5
 - scratch repair, 21-46
 - sealers, 3-5 to 3-6, 17-6, 17-12
 - seam filler material, 17-7, 17-9,

- 17-13
 - seam leveling, 21-46
 - seam polishing, 21-47
 - seam width, 17-6
 - serpentine, 17-1
 - setback subtops, *17-D.6*
 - shelves, *17-D.14*
 - shims, 17-5
 - shop drawings, 17-3, *17-D.17*
 - sidesplashes, *17-D.13*
 - sink flange, *17-D.8*
 - sink mounts, 17-4
 - slate, 17-2
 - soapstone, 17-2
 - spans, 17-4
 - spline joint reinforcement, *17-D.4*
 - splines, 17-11
 - stone slab layout, 17-3
 - stone tile, 17-2, 17-9
 - subcontractor responsibilities, 17-3
 - subtops, 17-3, 17-13, *17-D.8*, *17-D.14*, *17-D.15*
 - surface protection, 17-12 to 17-13
 - thicker slabs, *17-D.6*
 - thickness, 17-3
 - transport, 17-5
 - travertine, 17-2
 - undermount sink support, *17-D.8*
 - UV light exposure, 17-10, 17-13
 - course, defined, 23-8
 - coursed ashlar, 23-3
 - coursed veneer, defined, 23-8
 - cove base
 - See also* base
 - defined, 23-8
 - cove edge, *17-D.16*, *19-D.3*
 - cove molding, defined, 23-8
 - cove ogee edge, *17-D.16*, *19-D.3*
 - cove-Dupont edge, *17-D.16*, *19-D.3*
 - crack, defined, 23-8
 - crack isolation membranes, 13-7, 14-3
 - cracks
 - building movement, 21-22
 - chips, 21-22
 - in countertops, 17-11 to 17-12
 - defined, 21-22
 - excessive loading, 21-22
 - granite, 21-48
 - impact cracks, 21-22
 - improper installation, 21-22 to 21-23
 - macro-cracks, 21-45 to 21-46
 - micro-cracks, 21-45
 - cramps
 - defined, 23-8
 - granite, 5-3
 - marble, 7-3 to 7-4
 - non-ferrous, 10-3
 - onyx, 7-3 to 7-4
 - quartz-based stone, 8-3
 - serpentine, 9-4
 - slate, 10-3
 - creep. *See* hysteresis
 - cross cut stones
 - filling, 3-2
 - serpentine, 9-13
 - travertine, 12-11
 - cross-bedding, defined, 23-8
 - cross-cut, defined, 23-8
 - crowfoot (stylolite), defined, 23-26
 - crushing loads, 4-5
 - crypt, *14-D.15*
 - crystal structure, translucence, 7-21
 - crystalline quartz, physical properties, 8-7 to 8-8
 - crystallization
 - defined, 21-64
 - polishing pads, 21-64 to 21-65
 - popularity, 21-65
 - process, 21-65
 - cubic sills
 - bonding, 18-3
 - color, 18-3
 - corrosion-resistant metals, 18-3
 - fabrication, 18-3
 - finishes, 18-3
 - full mortar method, 18-4
 - installation, 18-4
 - oil-based putty, 18-3, 18-4
 - sealants, 18-3, 18-4
 - sizes, 18-3
 - thickness, 18-3
 - cubic stone, defined, 23-8
 - cultured marble, defined, 23-8
 - cup wheel, defined, 23-8
 - curbing, defined, 23-8
 - cure time, defined, 23-8
 - curtain walls, defined, 23-8, 23-9
 - cushion, defined, 23-8
 - customer communication about
 - countertops, 17-2 to 17-3, 17-13
 - cut stone, defined, 23-8
 - cut-to-size stones, defined, 13-1, 14-1
 - cutouts
 - countertops, 17-5
 - stone tile countertops, 17-9
 - cutting
 - for anchors
 - granite, 5-4
 - limestone, 6-4 to 6-5
 - marble and onyx, 7-4
 - quartz-based stone, 8-4
 - serpentine, 9-5
 - slate, 10-4
 - travertine, 12-4
 - for other trades
 - granite, 5-4
 - limestone, 6-5
 - marble and onyx, 7-4
 - quartz-based stone, 8-4
 - serpentine, 9-5
 - slate, 10-4
 - soapstone, 11-3
 - travertine, 12-4 to 12-5
 - cyanoacrylate (CA) glue, 21-40
 - adhesives and patching materials, 21-41 to 21-42
 - properties, 21-49
 - cycle time, defined, 23-9
- ## D
- damage prevention
 - adjacent surfaces, 21-25
 - building content, 21-25
 - damage types, for repairs, 21-43
 - damaged stone, repairing
 - granite, 5-3
 - limestone, 6-2
 - marble, 7-2
 - onyx, 7-2
 - quartz-based stone, 8-2
 - serpentine, 9-2 to 9-3
 - slate, 10-2
 - soapstone, 11-2
 - sticking, 9-2
 - travertine, 12-2
 - damp proofing
 - defined, 23-9
 - limestone, 6-11
 - travertine, 12-14
 - dead load
 - See also* live load
 - defined, 23-9
 - deflection, 13-5
 - backup stair treads, 14-13
 - cementitious backer units flooring, 14-9 to 14-10
 - flooring, 14-9
 - stair treads, 14-13
 - steam rooms and showers, 16-8
 - wood substrate flooring, 14-9
 - deicing chemicals
 - defective work, granite, 5-3
 - limestone, 6-13
 - quartz-based stone, 8-2

- serpentine, 9-2
 - travertine, 12-13
 - demi bullnose edge, *17-D.16, 19-D.3*
 - dense limestone
 - defined, 21-12
 - effective techniques, 21-12
 - density, 4-1
 - defined, 21-68
 - granite, 5-11
 - limestone, 6-12
 - marble and onyx, 7-17
 - quartz-based stone, 8-11
 - serpentine, 9-13
 - slate, 10-10
 - travertine, 12-12
 - water absorption, 4-3
 - dentil course, defined, 23-9
 - dentil, defined, 23-9
 - derrick, defined, 23-9
 - design considerations, 3-3, 17-10
 - detrital sedimentary stone, 1-1
 - diabase, 5-9
 - diamond
 - as abrasive, 21-29
 - defined, 23-9
 - dressings, 21-53
 - hardness, 17-10, 17-12, 21-2
 - diamond gang sawn finish, 12-7
 - diamond gauged finish, 10-9
 - diamond match pattern, *7-D.3*
 - defined, 23-9
 - diamond wire brushes, 21-37
 - diamond wire saw, defined, 23-9
 - die, *23-7, 23-18, 23-19*
 - defined, 23-9
 - digital inventory management, defined, 23-9
 - digital layout application, defined, 23-9
 - digital templating, defined, 23-9
 - dimension stone
 - defined, 23-9
 - flexure testing, 4-7
 - "Dimension Stone Anchorage; Theory, Practice, & Components," 21-18
 - diorite, 5-9
 - disc hangers for soffits, *14-D.18*
 - disclaimer, suggested, xii
 - dishing, marble and onyx, 7-21
 - dispensing tools, 21-43
 - distortion of stone in exterior application, 3-4
 - documentation of customer communication, 17-2 to 17-3
 - dolomite, 6-8 to 6-9, 7-8
 - abrasion resistance, 24-4
 - absorption of stone, 24-4
 - calcite vs., 6-9
 - compressive strength, 24-4
 - defined, 23-9
 - density, 24-4
 - flexural strength, 24-4
 - hardness, 6-9
 - modulus of rupture, 24-4
 - physical properties, 24-4
 - solubility, 6-9
 - water absorption, 24-4
 - dolomitic limestone, defined, 23-9
 - dolostone (dolomite), defined, 23-9
 - double chamfer edge, *17-D.16, 19-D.3*
 - double cove edge, *17-D.16, 19-D.3*
 - double pencil round edge, *17-D.16, 19-D.3*
 - double radius edge, *17-D.16, 19-D.3*
 - dovetail L straps, *14-D.23*
 - dovetail slot, defined, 23-9
 - dovetail split-tail straps, *14-D.23*
 - dovetail straps, *14-D.23*
 - dovetail twisted straps, *14-D.23*
 - dowelling, 21-8
 - dowels, *14-D.23, 14-D.24*
 - defined, 23-9
 - granite, 5-3
 - marble, 7-3 to 7-4
 - non-ferrous, 10-3
 - onyx, 7-3 to 7-4
 - quartz-based stone, 8-3
 - serpentine, 9-4
 - slate, 10-3
 - stainless steel, in stair treads, *13-D.6 to 13-D.8*
 - stair treads, *13-D.6 to 13-D.8*
 - down washed lighting, 14-17
 - downward crack, repairs, 21-44
 - drafted margin (*British*), defined, 23-9
 - drains, 21-20
 - drawings, shop
 - countertops, 17-3
 - granite, 5-2 to 5-3
 - limestone, 6-2
 - marble, 7-2
 - onyx, 7-2
 - quartz-based stone, 8-2
 - serpentine, 9-2
 - slate, 10-2
 - soapstone, 11-2
 - travertine, 12-2
 - dressings, defined, 21-48, 21-53, 23-9, 23-10
 - drilling
 - for anchors
 - granite, 5-4
 - limestone, 6-4 to 6-5
 - marble and onyx, 7-4
 - quartz-based stone, 8-4
 - serpentine, 9-5
 - slate, 10-4
 - travertine, 12-4
 - for other trades
 - granite, 5-4
 - limestone, 6-5
 - marble and onyx, 7-4
 - quartz-based stone, 8-4
 - serpentine, 9-5
 - slate, 10-4
 - soapstone, 11-3
 - travertine, 12-4 to 12-5
 - drip stone, defined, 23-10
 - drips
 - defined, 23-10
 - granite, 5-4
 - limestone, 6-4
 - marble and onyx, 7-4
 - quartz-based stone, 8-3
 - serpentine, 9-4
 - slate, 10-3 to 10-4
 - soapstone, 11-3
 - travertine, 12-4
 - dry assembly of countertops, 17-5
 - dry cleaning, 21-84
 - dry climate and limestone exterior, 3-4
 - dry pack, defined, 16-2
 - dry seam, defined, 23-10
 - dry stack, defined, 23-10
 - dry stack veneer, *14-D.22*
 - dry weight and specific gravity, 4-4 to 4-5
 - dry-lay, 13-1, 14-3
 - dry-pack mortar, 13-8 to 13-9, 13-12 to 13-13, 14-6 to 14-7
 - drywall, mold and mildew, 16-2
 - dual finish, defined, 23-10
 - Dupont edge, *17-D.16, 19-D.3*
 - durability, defined, 23-10
 - durability of exterior application, 3-4
 - dust restrictions, 21-26
 - Dutchman, defined, 23-10
 - dyes, 21-7
 - dynamic coefficient of friction, 4-9
- ## E
- Earth Day, v
 - eased edge, defined, 23-10
 - eaves, defined, 23-10
 - edge chiseling tool, defined, 23-10
 - edge profiles, *19-D.3*

- countertops, 17-4
 - defined, 23-10
 - finishing, 17-5
 - edge treatment for stone tile countertops, 17-9
 - edges, tolerances, 22-6
 - efflorescence, 13-19, 14-17, 21-20
 - to 21-21, 21-22, 21-81 to 21-82
 - defined, 23-10
 - granite, 5-13 to 5-14
 - limestone, 6-14 to 6-15
 - marble and onyx, 7-19, 7-20
 - quartz-based stone, 8-13 to 8-14
 - serpentine, 9-15 to 9-16
 - slate, 10-12 to 10-13
 - subsurface water, 21-26
 - travertine, 12-14
 - elastic distortion and exterior application, 3-4
 - elastomeric sealant for countertops, 17-7, 17-9
 - electrical power, commercial and historical restoration, 21-85
 - electrical properties of crystalline quartz, 8-8
 - elemental composition, oceanic vs. continental stone, 1-3
 - elevation, defined, 23-10
 - embellishments, corner, 17-4
 - enameled cast iron sinks, support details, 17-D.8
 - enclinal marble, defined, 23-10
 - end match pattern, 7-D.3
 - end slip pattern, 7-D.2
 - energy and atmosphere, viii
 - engineered stone, defined, 23-10
 - engineering, 14-11
 - entablature, 23-7, 23-8, 23-12
 - defined, 23-10
 - entasis
 - defined, 23-10
 - free-standing columns, 14-D.13
 - epidote, in marble, 7-9
 - epoxy, 21-7
 - adhesives and patching materials, 21-41
 - properties, 21-49
 - epoxy resin, 21-8
 - countertops, 17-7, 17-9, 17-10
 - defined, 23-10
 - erection, defined, 23-10
 - etched, defined, 23-10
 - etching, 21-23
 - ethics, xiv
 - exfoliation, defined, 23-11
 - expansion anchor, 14-D.1, 14-D.4
 - defined, 23-11
 - expansion bolts for soffits, 14-D.18
 - defined, 23-11
 - expansion gaskets, 18-1
 - expansion joints, 13-6
 - defined, 21-19, 23-11
 - exterior cubic stone coping and walls, 18-2
 - exterior stone veneer, 14-D.9
 - granite, 5-4, 5-6
 - limestone, 6-7
 - location, 14-9
 - marble and onyx, 7-4, 7-7
 - quartz-based stone, 8-3, 8-6
 - serpentine, 9-4, 9-8
 - slate, 10-6
 - soapstone, 11-3
 - travertine, 12-4, 12-6 to 12-7
 - exposed edges
 - countertops, 17-6
 - furniture and tops, 19-1
 - showers, residential, 16-10
 - showers, residential, 16-D.10
 - steam rooms and showers, 16-10
 - exposed face, defined, 23-11
 - exterior application
 - considerations, 3-3 to 3-4
 - diagnostic considerations, 21-24
 - durability, 3-4
 - inappropriate stones, 3-4
 - test data, 3-4
 - exterior cubic stone coping and walls
 - backup walls, 18-1
 - bond stones, 18-1
 - bonding, 18-1
 - color, 18-1
 - coping details, 18-D.1
 - expansion gaskets, 18-1
 - expansion joints, 18-2
 - fabrication, 18-1
 - finishes, 18-1
 - flashing details, 18-D.1
 - full mortar method, 18-2
 - joint width, 18-2
 - load-bearing walls, 18-1
 - oil-based putty, 18-1, 18-2
 - parapet details, 18-D.1
 - preparation, 18-2
 - exterior pavers
 - color, 14-5
 - concrete subsurface, 14-5 to 14-6
 - flexural strength, 14-5, 14-6
 - installation, 13-D.1 to 13-D.2, 14-5 to 14-6
 - joints, 14-5
 - mortar bed, 14-5 to 14-6
 - pedestal system, 14-6
 - sand bed, 14-6
 - traffic after installation, 14-5
 - exterior stone cleaning, 21-79 to 21-80
 - exterior stone maintenance, 21-79
 - exterior stone selection, 4-10
 - exterior stone stresses, 3-3 to 3-4
 - exterior stone veneer
 - adhered veneer, 14-13 to 14-14
 - blind connections, 14-D.5
 - colors, 14-2
 - corners, standard, 14-D.9
 - expansion joints, 14-D.9
 - extraction testing for heavy metals, 2-4
 - fabrication, 14-2
 - finishes, 14-2
 - independently supported, 14-11 to 14-12
 - installation, 14-11 to 14-14, 14-D.1 to 14-D.7
 - rebated bearing, 14-D.6
 - reglets, 14-D.9
 - restraint anchorage, 14-D.7
 - split-tail anchor, 14-D.2
 - stacked, 14-12
 - steel T, 14-D.1 to 14-D.3
 - stone relief, rebated bearing, 14-D.6
 - vertical surfaces, 14-11 to 14-14
 - eye rod and dowel, 14-D.25
- F**
- fabricated, defined, 23-11
 - fabrication
 - countertops, 17-5
 - cubic sills, 18-3
 - exterior cubic stone coping and walls, 18-1
 - furniture and tops, 19-2
 - quartz-based stone, 8-11
 - shower partitions, 16-5
 - showers, residential, 16-10
 - steam rooms and showers, 16-10
 - toilet partitions, 16-3
 - tolerances, 22-5 to 22-6
 - urinal partitions, 16-4
 - window stools, 18-3
 - face size, tolerances, 22-5
 - face, defined, 23-11
 - fall off. *See* remnant (23-21)
 - fascia, defined, 23-11
 - feed rate, defined, 23-11
 - feldspar, 5-8, 17-12

- defined, 23-11
- felsic stone, 1-3
- ferruginous, defined, 23-11
- fiberglass backing, defined, 23-11
- fiberglass mesh backing, 13-18, 14-16, 21-8 to 21-9
 - adhesive, countertops, 17-11
- field identification, 21-5
- field measurements for countertops, 17-3 to 17-4
- field repair, 13-2, 14-3
- fieldstone, defined, 23-11
- filled finish (travertine), 12-10
- filler strip (backer rod), defined, 23-3
- fillers
 - anchor prep, 14-6
 - maintenance, 21-76
- filling, defined, 23-11
- fine rubbed finish, 3-2, 5-7
- finest, defined, 23-11
- finish, defined, 23-11
- finished work, protection of, 13-17 to 13-18
- finishes, 3-2, 13-3
 - countertops, 17-2
 - cubic sills, 18-3
 - exterior cubic stone coping and walls, 18-1
 - exterior pavers, 14-5
 - flooring, 14-8
 - foot traffic, 14-1
 - furniture and tops, 19-2
 - granite, 5-6 to 5-7, 5-10, 21-61 to 21-62
 - identification, 21-5 to 21-6
 - limestone, 6-10, 21-58
 - marble, 21-58
 - marble and onyx, 7-14
 - non-planar, 13-6
 - pavers, 14-1
 - precast concrete panels, 20-1
 - quartz-based stone, 8-10
 - serpentine, 9-12
 - shower partitions, 16-5
 - slate, 10-3, 10-9
 - soapstone, 11-3
 - stair treads, 14-13
 - stone veneer panels, 20-1
 - thresholds, 14-11
 - toilet partitions, 16-3
 - translucence, 7-21
 - travertine, 12-7, 21-58
 - urinal partitions, 16-4
 - window stools, 18-3
- finishing tools, 21-43
- fire ratings, 14-10 to 14-11
- fire resistance
 - limestone, 6-13
 - marble and onyx, 7-17
 - quartz-based stone, 8-12
 - serpentine, 9-15
 - slate, 10-11
 - soapstone, 11-6
 - travertine, 12-13
- fireplace facings
 - details, *14-D.19, 14-D.20*
 - header, *14-D.19, 14-D.20*
 - hearth, *14-D.19, 14-D.20*
 - installation, 14-15
 - leg, stone, *14-D.20*
 - mantel, stone, *14-D.19*
 - mantel, wood, *14-D.20*
 - masonry fireplace, *14-D.19, 14-D.20*
 - surround, stone, *14-D.19*
 - surround, wood, *14-D.20*
- fissures
 - countertops, 17-11
 - defined, 23-11
- flagstone, defined, 23-11
- flamed finish (thermal finish), 3-2
 - defined, 21-6, 23-26
 - granite, 5-7, 21-62
 - limestone, 6-10
- flashing, 14-4
- flashing and limestone, 6-4
- flashing details, exterior cubic stone coping and walls, *18-D.1*
- flat installation of stone tile countertops, 17-9
- flat strap hangers for soffits, *14-D.18*
- flatness, tolerances, 22-6
- fleuri cut, 23-27. *See also* cross cut
 - defined, 23-11, 23-12
 - filling, 3-2
 - marble and onyx, 7-16
 - serpentine, 9-13
 - travertine, 12-11, 24-4 and voids, 13-19
 - veneer cutting, *7-D.1*
- flexural strength, 4-6. *See also* modulus of rupture
 - defined, 23-12
 - granite, 5-11
 - limestone, 6-12
 - marble and onyx, 7-17
 - pedestal supported support systems, 13-13
 - quartz-based stone, 8-11
 - serpentine, 9-13
 - slate, 10-10
 - travertine, 12-12
- flexure testing
 - dimension stone, 4-7
 - limitations, 4-7
 - slate, 4-7
 - thickness, 21-18
- flint, 8-7, 8-9
- floor drains, *16-D.6 to 16-D.7*
- floor installation
 - marble and onyx, 7-5 to 7-6
 - serpentine, 9-6 to 9-7
- floor machines, 21-27 to 21-28
 - attachments, 21-27
 - diamond honing and polishing, 21-27
 - drive plates, 21-28
 - floating heads, 21-28
 - mono-rotary machines, 21-27
 - planetary machines, 21-27 to 21-28
 - rigid heads, 21-28
- floor-mounted shower partitions, 16-6
- floor-mounted toilet partitions, *16-D.1*
- flooring
 - adjacent floors and damage, 21-25
 - alkalinity, 14-7
 - cast-in-place concrete, 13-5
 - cementitious backer units, 13-11
 - cleaning
 - marble and onyx, 7-6
 - serpentine, 9-6
 - color, 14-8
 - concrete subsurface, 14-9
 - concrete, cast in place, 13-5
 - defined, 23-12
 - deflection of, 13-5, 14-8, 14-9
 - finishes, 13-3, 14-8
 - float the floor, 21-54
 - grout, 14-7
 - heated floor systems, 13-16 to 13-17, 14-10
 - high-traffic exteriors, 3-4
 - hollow sound, 13-18
 - installation, *13-D.3 to 13-D.4*, 14-8 to 14-10
 - installation methods, 14-7
 - installation references, 13-14
 - joint width, 13-5 to 13-6
 - lighting, 13-19
 - marble and onyx, 7-6
 - moisture, 13-18
 - refinishing, abrasive bonds, 21-32 to 21-34
 - serpentine, 9-6 to 9-7
 - slate, 10-10
 - strength considerations, 4-7
 - thickness, 13-2

- traffic after installation, 7-6, 9-6, 14-7
- transitions, 13-18
- travertine, 12-11
- wood subfloor, 14-9
- fluorite, hardness, 21-2
- flute, defined, 23-12
- fossils, 6-9 to 6-10
- fracture, defined, 23-12
- fracturing
 - crystalline quartz, 8-7 to 8-8
 - texture of quartz-based stone, 8-9
- frame construction
 - heated floor systems, 14-10
 - window stools, *18-D.2*
- free-standing units, shower partitions, 16-6
- freestone, defined, 23-12
- freeze/thaw cycles and exterior applications, 3-4
- freeze/thaw issues, 21-24
- friction, 13-4 to 13-5
- frieze, *23-7, 23-8, 23-10*
 - defined, 23-12
- front-end loader, defined, 23-12
- full bullnose edge, *17-D.16, 19-D.3*
- full mortar method
 - steam rooms, 16-9, 16-11
 - steam showers, 16-9, 16-11
 - exterior cubic stone coping and walls, 18-2
 - cubic sills, 18-4
- furniture, moving, 21-25
- furniture and tops
 - base design, 19-1
 - bevels, 19-1
 - color, 19-2
 - conference table, *19-D.1, 19-D.2*
 - exposed edges, 19-1
 - fabrication, 19-2
 - finishes, 19-2
 - installation, 19-2
 - laminated aprons, 19-1
 - marble and onyx, 19-1
 - oil-based putty, 19-1
 - overhangs, 19-1
 - plywood subtops, 19-1, *19-D.1*
 - quirk miters, 19-1
 - radius of rounded edges, 19-1
 - sealing, 19-1
 - sizes, 19-2
 - slate, 19-1
 - spans, 19-1
 - thickness, 19-1
 - travertine, 19-1
 - tube steel supports, *19-D.1*

G

- gabbro, 5-9, 21-15
- gabbro, defined, 23-12
- gallet (*British*), defined, 23-12
- gang saw, 5-10, 7-16, 9-13
 - defined, 23-12
- garnet, 5-9
- gauge
 - See also* calibration
 - defined, 23-12
- generic movement joints, defined, 21-19
- geographic methods, 13-17
- geographical variation, 13-17, 14-17
- geological classification, sealers, 21-69
- Gissen, David, v
- glass seam
 - See also* dry seam
 - defined, 23-12
- gloss meter, defined, 23-12
- gloss, variation in, 13-19, 14-17
- gneiss, 5-9, 21-15
 - defined, 23-12
- grain, defined, 23-12
- granite
 - abrasion, 5-11
 - abrasion resistance, 5-12, 24-4
 - absorption of stone, 5-11, 24-4
 - adhesive, 5-3
 - anchorage, 5-7
 - anchors, 5-3
 - ashlar facing, 5-8
 - back-checking, 5-4
 - backs of pieces, 5-4
 - bacteria, 5-14
 - bed width, 5-8
 - bending strength, 5-12
 - black granite, 5-9, 23-4
 - bolted connections, back-checking, 5-4
 - carving, 5-4
 - caulking, 5-6
 - cleaning, 5-7
 - coefficient of thermal expansion, 5-11
 - color, 5-9
 - commercial definition, 23-13
 - composition of, 5-8 to 5-9
 - compressive strength, 5-11 to 5-12, 24-4
 - countertop polishing
 - cleaning, 21-64
 - equipment, 21-62
 - polishing, 21-64
 - refinishing, 21-63 to 21-64
 - sealing, 21-64
 - surface preparation, 21-62 to 21-63
 - countertops, 3-5 to 3-6
 - cubic sills, 18-3
 - damaged stone, repairing, 5-3
 - defined, 21-15, 23-13
 - density, 5-11, 24-4
 - drips, 5-4
 - edging, 21-59 to 21-60
 - effective techniques, 21-15 to 21-16
 - efflorescence, 5-13 to 5-14
 - enhanced, 5-15
 - epoxy filling, 5-15
 - expansion joints, 5-6
 - exterior application, 3-4
 - exterior cubic stone coping and walls, 18-1
 - face filling, 5-15
 - finishes, 5-4, 5-6 to 5-7, 5-10
 - fire resistance, 5-12
 - fleuri cut, 3-2
 - flexural strength, 5-1, 24-41
 - flooring, 5-10
 - gabbro, 21-15
 - genuine, 1-4
 - geological classification, 5-8 to 5-9, 21-70
 - gneiss, 5-9, 21-15
 - hardness, 5-9, 5-12
 - identification, 21-15
 - joint width, 5-8
 - lippage removal, 21-59
 - mineral components of, 5-8 to 5-9
 - minimum safety factors, 5-7
 - modulus of elasticity, 5-11
 - modulus of rupture, 5-11, 24-4
 - moisture absorption, 5-12
 - moldings, 5-4
 - mortar, 5-3
 - mortar setting of, 5-5
 - orthoclase feldspar, 5-8
 - orthoquartzite vs., 5-9
 - packing and loading, 5-5
 - panel, 5-4
 - physical properties, 5-10 to 5-11, 24-4
 - pitting, 5-14, 17-12
 - plagioclase feldspar, 5-8
 - polyester filling, 5-15
 - protection of, 5-6 to 5-8
 - quartz, 5-9
 - quartzite vs., 5-9
 - radon, 5-14
 - refinishing, surface preparation, 21-59
 - refinishing and polishing

- considerations, 21-61
- edging, 21-59 to 21-60
- equipment, 21-59
- grinding, 21-60
- honing, 21-61
- lippage removal, 21-59
- other finishes, 21-61 to 21-62
- polishing, 21-61
- process, 21-58 to 21-59
- sealing, 21-61
- transition step, 21-60
- resin filling, 5-15
- resin-treated, 3-6
- rigid resin diamond abrasives, 21-47
- safety factors, 5-12 to 5-13
- sampling, 5-10
- sawn backs, 5-9
- scientific definition, 23-13
- sealant joints, 5-6 to 5-7
- sealants, 5-3
- sealers, 3-5 to 3-6
- seams or cracks, 21-48
- seismic considerations, 5-13
- seismic loads, 5-13
- sizes, 5-10
- staining, 5-9, 5-13 to 5-14
- stair treads, 14-13
- storage, 5-5
- strength, 5-11 to 5-12
- texture, 5-10
- thickness, 5-7, 5-10
- thresholds, 14-11
- tinting, 5-15
- turbo-style resin diamond abrasives, 21-47
- usage tips, 5-10
- veneer cutting, 5-10
- veneer facing, 5-9
- washes, 5-4
- water absorption, 24-4
- weep tubes, 5-6
- wind loads, 5-13
- window stools, 18-3
- granite and quartzite
 - Giallo Ornamental, 21-15
 - Kashmir, 21-15
 - Santa Cecilia, 21-15
- granitic lava, 1-3
- granitization, 5-9
- granular, defined, 23-13
- granular bed method, 13-14
- gravity load and exterior applications, 3-3
- green building, v to xi
 - history, v to vii
 - stone and, ix to x
- green colored stone, 14-16
 - adhesives for, 13-18
- green references, xi
- greenstone, defined, 23-13
- grind, defined, 23-13
- grinding
 - granite refinishing and polishing, 21-60
 - machine control, 21-48
 - MTL refinishing and polishing
 - first grinding, 21-54 to 21-55
 - light grinding, 21-55 to 21-56
- grinding tools, 21-43
- grout
 - acrylic modified portland cement grout, 14-8
 - adhesion problems, 21-26
 - color, 13-9 to 13-10, 14-8
 - countertops, 17-9
 - defined, 23-13
 - flooring, 14-7
 - grout inspection, 21-24
 - horizontal applications, 13-9 to 13-10
 - joint width, 14-2
 - latex modified portland cement grout, 14-8
 - maintenance, 21-76
 - polymer modified portland cement grout, 14-8
 - sanded portland cement grout, 14-7
 - staining, 14-8
 - stains, 21-22, 21-26
 - steam rooms, 16-9, 16-12
 - steam showers, 16-9, 16-12
 - unsanded portland cement grout, 14-7 to 14-8
 - veneer cavities, 14-4
- guillotine, defined, 23-13
- guillotining of slabs, 8-11
- gypsum, 14-16
 - formation from calcite, 7-12
 - hardness, 21-2
- gypsum-based underlayment for stone tiles, 13-5
- gypsum molding plaster, serpentine, 9-7
- gypsum wall board
 - exterior stone veneer, *14-D.8*
 - interior cladding, *14-D.10* to *14-D.11*
- half bullnose edge, *17-D.16*
- halite, defined, 23-13
- handheld machines
 - variable speed machines, 21-28
 - pad drivers, 21-28 to 21-29
- hardness, 21-2 to 21-3
 - absolute, 21-3
 - crystalline quartz, 8-7
 - defined, 21-2, 23-13
 - dolomite, 6-9
 - foot traffic, 14-1
 - limestone, 6-9
 - Mohs scale, 17-10, 17-12, 21-2, 24-2
 - pavers, 14-1
 - pyrite, 7-10
 - sealers, 21-69
 - soapstone, 11-5
 - stair treads, 14-13
- hazing, 21-22, 21-26
- head, defined, 23-13
- header for fireplace facings, *14-D.19, 14-D.20*
- hearth for fireplace facings, *14-D.19, 14-D.20*
- hearth stone, defined, 23-14
- hearth, defined, 23-14
- heat retention of soapstone, 11-5
- heated floor systems, 13-16 to 13-17, *13-D.4*
- high angle of incidence for lighting, 13-19
- high traffic environments, diagnostic considerations, 21-24
- high-traffic floor areas, 13-4
 - exterior, 3-4
 - interior, 3-5
- historic restoration
 - additional resources, 21-121 to 21-122
 - labor restrictions, 21-87
 - payment, 21-88
 - rules and regulations, 21-85
 - work approval, 21-88
- hollow sounds, 14-1 to 14-2, 21-26
- horizontal surfaces, 13-18
 - flooring, 13-18
- honed, defined, 23-14
- honed finish, 3-2, 18-1, 19-2
 - countertops, 17-2
 - defined, 21-5, 21-75
 - granite, 5-6, 21-61 to 21-62
 - limestone, 6-10
 - marble and onyx, 7-3, 7-14
 - MTL, 21-58
 - serpentine, 9-12
 - slate, 10-9
 - travertine, 12-7, 12-10

H

hairpin precast anchor, *14-D.25*

- honing
 - granite refinishing and polishing, 21-61
 - machine control, 21-48
 - MTL refinishing and polishing, 21-56 to 21-57
 - honing pads, miscellaneous, 21-36
 - honing tools, 21-43
 - hooked bolt, *14-D.25*
 - horizontal applications
 - ASTM standards, 4-3
 - installation, 14-1 to 14-14
 - interior surfaces, 3-5
 - horizontal surfaces
 - abrasion resistance, 13-4
 - carving, 13-2
 - cementitious backer units, 13-11
 - colors, 13-3
 - finishes, 13-3
 - friction, 13-4 to 13-5
 - grout, 13-9 to 13-10
 - hollow sound, 13-18
 - membranes, 13-7
 - sizes, 13-3
 - stone edges, 13-6
 - stone selection, 13-1
 - thickness, 13-2, 13-3
 - hornblende, 5-9, 11-5
 - hot mop, defined, 16-2
 - hot-tub environments, diagnostic considerations, 21-24
 - humidity and exterior applications, 3-4
 - hydrated lime
 - limestone, 6-3
 - travertine, 12-3
 - hydraulic cleaning, 21-84
 - hysteresis (thermal), 14-16
 - defined, 23-14
 - marble and onyx, 7-21, 7-19 to 7-20
- I**
- Iceland Spar, 7-11
 - IEC (International Electrotechnical Commission), 2-3
 - igneous, defined, 21-1
 - igneous rock, 1-1
 - cleaning and maintenance, 21-78
 - geological classification, 21-70
 - pitting, 17-12
 - igneous stone, formation, 1-4
 - igneous, defined, 23-14
 - ILI (Indiana Limestone Institute of America)
 - defined, 23-14
 - publications, 6-1
 - impregnators (penetrating sealers), 17-12 to 17-13
 - defined, 21-6 to 21-7, 23-14
 - inches to millimeters, 24-1
 - incise, defined, 23-14
 - Indiana Limestone Institute of America (ILI)
 - defined, 23-14
 - publications, 6-1
 - inscription, defined, 23-14
 - inspection, 14-3
 - for repairs, 21-43
 - installation
 - attachment method, 21-17
 - cold weather, 12-6
 - condition, maintenance, 21-76
 - countertops, 17-5 to 17-6
 - cubic sills, 18-4
 - existing installation, 21-17 to 21-18
 - exterior installation, maintenance, 21-76
 - exterior stone veneer, 14-11 to 14-14
 - furniture and tops, 19-2
 - granite, 5-6 to 5-7
 - high rise cladding, maintenance, 21-77
 - interior installation, maintenance, 21-76
 - limestone, 6-5 to 6-7
 - location, maintenance, 21-76
 - marble and onyx, 7-5 to 7-7
 - mechanical anchors, 21-18
 - precast concrete panels, 20-2
 - quartz-based stone, 8-5 to 8-6
 - serpentine, 9-5 to 9-8
 - shower partitions, 16-5 to 16-6
 - showers, residential, 16-10 to 16-11
 - slate, 10-4 to 10-6
 - soapstone, 11-3 to 11-4
 - steam rooms and showers, 16-11 to 16-12
 - stone tile countertops, 17-9
 - stone veneer panels, 20-2
 - tile, 21-18
 - toilet partitions, 16-3
 - tolerances, 22-7 to 22-8
 - travertine, 12-5 to 12-7
 - urinal partitions, 16-4
 - window stools, 18-4
 - interior application
 - considerations, 3-4 to 3-5
 - selection criteria, 3-4 to 3-5
 - water resistance, 3-5
 - interior cladding
 - anchorage, 14-14 to 14-15
 - anchors, wire, *14-D.10*
 - beveled block joint, *14-D.16*
 - bracket detail, *14-D.15*
 - butt joint, *14-D.16*
 - column, free-standing
 - anchors, *14-D.12*
 - battered splay, *14-D.14*
 - entasis, *14-D.13*
 - joints, *14-D.13* to *14-D.14*
 - corner block joint, *14-D.16*
 - corner cove joint, *14-D.16*
 - corner detail, *14-D.16*
 - crypt, *14-D.15*
 - external corners, *14-D.16*
 - fire rated wall, *14-D.11*
 - gypsum wall board, *14-D.8*, *14-D.10* to *14-D.11*
 - installation, 14-14 to 14-15
 - internal corners, *14-D.16*
 - metal studs, *14-D.10*, *14-D.11*
 - molded joint, *14-D.16*
 - molded trim, *14-D.12*
 - quirk miter joint, *14-D.16*
 - rabbeted joint, *14-D.16*
 - rosette detail, *14-D.15*
 - rosette fasteners, *14-D.15*
 - stone slide, *14-D.15*
 - strap anchored, *14-D.8*
 - wall facing details, *14-D.10* to *14-D.11*
 - wet areas, 14-16
 - wire anchored, *14-D.8*
 - interior panels
 - adhered systems, 14-15
 - anchored systems, 14-14 to 14-15
 - installation, 14-14 to 14-15
 - interior stone base, details, *14-D.17*
 - interior veneer
 - cement backer board, *14-D.8*
 - gypsum wall board, *14-D.8*
 - marble and onyx, 7-6
 - restraint anchorage, *14-D.8*
 - serpentine, 9-7
 - intermediate stone, Andesite, 1-3
 - International Electrotechnical Commission (IEC), 2-3
 - International Organization for Standardization (ISO), 2-3
 - inward crack, for repairs, 21-44
 - iron oxides as cementing material, 1-6
 - ISO (International Organization for Standardization), 2-3
 - ISO/IEC Guide 25, 4-2

isolation joint, defined, 21-19, 23-14

J

J.O.S. system, 21-84

jamb, 23-14

jasper (chert), 8-9

jet washed finish, 5-7

joinery

alignment, 21-20

layout for countertops, 17-4

joint, defined, 23-14

joint filler

countertops, 17-7, 17-9

stone tile countertops, 17-2

joint filling, 17-6

joint sealants, 14-8 to 14-9

maintenance, 21-76

joint width, 13-5 to 13-6, 14-9 to 14-10

countertops, 17-6

exterior cubic stone coping and walls, 18-2

granite, 5-4, 5-9

marble and onyx, 7-4

pavers, 14-2

quartz-based stone, 8-3

serpentine, 9-4

showers, residential, 16-7 to 16-8, 16-11

slate, 10-3

stone tile countertops, 17-9

tolerances, 21-20, 22-7

travertine, 12-4

jointing scheme, defined, 23-14

joints

sink, 17-D.4

slate, 10-3

types of, 21-18 to 21-19

width tolerances, 21-20, 22-7

joints, free-standing column, 14-D.13 to 14-D.14

exterior pavers, 14-5, 14-6

granite, 5-4

pressure relieving, 14-D.6

joints, open, 13-13 to 13-14

K

kaolinite, defined, 23-14

kerf, 5-4

defined, 23-14

rebated kerf, 23-21

Kessler abrasion testing, 4-8

keystone

defined, 23-14

Roman arch, 23-22

kitchen layouts and countertops,

17-D.1 to 17-D.2

shop drawings, 17-D.17

knife edge, 17-D.16, 19-D.3

L

L bar, 14-D.25

L straps, 14-D.23

L stud and disc, 14-D.24

L-spline anchors, 14-D.18

labor assignment, 14-1

labor restrictions, 21-87

laminated aprons for furniture and tops, 19-1

laminated edge, 17-D.16, 19-D.3

lamination, defined, 23-14

laser, defined, 23-14

lathe, defined, 23-15

lavatory tops, 3-5

See also countertops

backsplashes, 17-D.12

vanities, 17-D.11

layout for countertops, 17-5

joinery layout, 17-4

lead buttons, defined, 23-15

Leadership in Energy and Environmental Design (LEED), vii, viii to ix

leather finish, countertops, 17-2

LEED (Leadership in Energy and Environmental Design), vii, viii to ix

legs for fireplace facings, 14-D.20

length and area, conversion ratios, 24-2

lewis, defined, 23-15

lewis pins

defined, 23-15

granite, 5-4

limestone, 6-5

marble and onyx, 7-4

quartz-based stone, 8-4

serpentine, 9-5

slate, 10-4

travertine, 12-4

light colored stones

mortar, 13-9

portland cement, 14-7

setting beds, 13-18

light foot-traffic, 13-4

interior, 3-5

lighting, 13-19

commercial and historical restoration, 21-85

limestone

abrasion, 6-12

abrasion resistance, 6-13, 24-4

absorption of stone, 6-12, 24-4

anchorage, 6-6 to 6-7

anchors, 6-4

atmospheric agents, 6-13

back-checking, 6-4

backs of pieces, 6-4

Beaumaniere, 21-12

bolted connections, back-checking, 6-4

carving, 6-5

caulking, 6-7

clasts, 6-8

clay, 6-9

cleaning, 6-7, 21-14

coefficient of thermal expansion, 6-12

cold weather and installation, 6-6

color, 6-10

compressive strength, 6-12, 24-4

contact with soil, 6-15

countertops, 17-2

Crema Europa, 21-12

cubic sills, 18-3

damaged stone, repairing, 6-2

dampproofing, 6-11

deicing chemicals, 6-13

defined, 23-15

dense

defined, 21-12

effective techniques, 21-12

density, 6-12, 24-4

drips, 6-4

efflorescence, 6-14 to 6-15

expansion joints, 6-7

exterior application, 3-4

exterior cubic stone coping and walls, 18-1

finishes, 6-10

fire resistance, 6-13

flexural strength, 6-12, 24-4

flooring, 6-13

fossiliferous, 6-9 to 6-10

geological classification, 6-8 to 6-10, 21-70

hardness, 6-8, 6-13

horizontal applications, 6-6

hydrated lime, 6-3

installation, 6-5 to 6-7

metamorphosis to calcite, 7-9

modulus of elasticity, 6-12

modulus of rupture, 6-12, 24-4

moldings, 6-4

mortar, 6-3, 13-9, 14-7

mortar setting of, 6-6

packing and loading, 6-5

panel thickness, 6-4

- physical properties, 6-11 to 6-12, 24-4
 - plastic setting pads, 6-6
 - porous
 - defined, 21-12
 - effective techniques, 21-12
 - protection of, 6-8
 - repairing, 21-13 to 21-14
 - sampling, 6-11
 - sand, 6-3
 - sealant joints, 6-7
 - sealants, 6-3
 - seismic loads, 6-14
 - sizes, 6-11
 - snow melting chemicals, 13-19
 - stain prevention, 6-4
 - staining, 6-14 to 6-15
 - stair treads, 14-13
 - storage, 6-5
 - strength, 6-12 to 6-13
 - tensile strength, 6-11
 - texture, 6-10
 - thermal expansion, 6-15
 - thickness, 6-10 to 6-11
 - thresholds, 14-11
 - usage tips, 6-11
 - veining, 6-10
 - vener cutting, 6-11
 - washes, 6-4
 - water, 6-4
 - water absorption, 24-4
 - weep tubes, 6-7
 - white masonry cement, 6-3
 - white portland cement, 6-3
 - wind loads, 6-14
 - window stools, 18-3
 - limitations
 - precast concrete panels, 20-1
 - stone veneer panels, 20-1
 - limonite, 8-9
 - line (edge) polisher, defined, 23-15
 - liner blocks for countertops, 17-11
 - liners, defined, 23-15
 - lintel, 23-21
 - defined, 23-15
 - lippage
 - countertops, 17-6, 17-7
 - defined, 23-15
 - horizontal applications, 13-6
 - pavers, 14-3
 - removal of, 21-25
 - slate, 10-3
 - tolerances, 21-20, 22-7
 - vertical surfaces, 14-10
 - lithochemistry, 4-1 to 4-2
 - lithosphere, 1-2
 - live load
 - See also* dead load
 - defined, 23-15
 - load cell, defined, 23-15
 - load-bearing walls, 18-1
 - lug sill, defined, 23-15
- M**
- machine finish, defined, 23-15
 - machine gauged finish, 10-9
 - machine tooled finish
 - limestone, 6-10
 - travertine, 12-7
 - mafic stone, 1-3
 - magnesite, 6-8, 7-10, 9-10, 11-5
 - magnetite, 5-9, 9-11
 - maintenance
 - additional resources, 21-121
 - commercial cleaning and sealing, 21-78 to 21-79
 - countertops, 17-12 to 17-13
 - current products and procedures, 21-21
 - defined, 21-75, 23-15
 - purpose and benefits, 21-75 to 21-76
 - residential cleaning, 21-77 to 21-78
 - specifying, 3-8
 - mantels for fireplace facings, 14-D.19, 14-D.20, 23-14
 - mantle (Earth), 1-2
 - marble and onyx
 - See also* MTL (marble/travertine/limestone)
 - abrasion, 7-17
 - abrasion resistance, 7-17 to 7-18, 24-4
 - abrasive finish, 7-3
 - absorption of stone, 7-17, 24-4
 - accessory mineral variation, 7-10
 - adhesive, 7-3
 - anchorage, 7-7
 - anisotropic-hysteretic effects, 7-12 to 7-13
 - back-checking, 7-4
 - backs of pieces, 7-4
 - blend pattern, 7-D.2
 - bolted connections, back-checking, 7-4
 - book match pattern, 7-D.3
 - breccia, 21-14
 - brecciated veneer patterns, 7-D.3
 - burning, 21-13
 - calcite
 - abrasion resistance, 24-4
 - absorption of stone, 24-4
 - acid reaction, 7-11
 - anisotropy, 7-11 to 7-12
 - chemical properties, 7-10 to 7-11
 - cleavage, 7-11
 - color, 7-11
 - composition of, 7-11
 - compressive strength, 24-4
 - crystals, 7-10 to 7-11
 - density, 24-4
 - flexural strength, 24-4
 - Iceland Spar, 7-11
 - modulus of rupture, 24-4
 - optical character, 7-11
 - physical properties, 24-4
 - thermal hysteresis, 7-12 to 7-13
 - water absorption, 24-4
 - carving, 7-5
 - caulking, 7-7
 - cleaning, 7-7
 - coefficient of thermal expansion, 7-17
 - color, 7-8 to 7-9, 7-13
 - commercial definition, 23-15
 - compressive strength, 4-4, 7-17
 - countertops, 3-6, 17-1
 - cramps, 7-3 to 7-4
 - crystallizers, 21-36
 - cubic sills, 18-3
 - damaged stone, repairing, 7-2
 - defined, 23-15
 - density, 7-17, 24-4
 - diamond match pattern, 7-D.3
 - dishing, 7-21
 - distortion of stone, 7-12
 - dolomitic marble, 7-8 to 7-9
 - abrasion resistance, 24-4
 - absorption of stone, 24-4
 - compressive strength, 24-4
 - density, 24-4
 - flexural strength, 24-4
 - modulus of rupture, 24-4
 - physical properties, 24-4
 - water absorption, 24-4
 - dowels, 7-3 to 7-4
 - drips, 7-4
 - efflorescence, 7-19, 7-20
 - end match pattern, 7-D.3
 - end slip pattern, 7-D.2
 - expansion joints, 7-7
 - exterior cubic stone coping and walls, 18-1
 - face dimensions, 7-16
 - finishes, 7-3, 7-14
 - fire resistance, 7-17
 - fleuri cut, 7-16
 - flexural strength, 7-17, 24-4

flooring, 14-5
 finishes, 7-14
 installation, 7-5 to 7-6
 geological classification, 7-8 to 7-13, 21-70
 geological origin, 7-9 to 7-10
 green, 9-8 to 9-9, 9-10
 adhesive, 13-19
 group A, 7-15
 flooring, 14-5
 furniture and tops, 19-1
 pavers, 14-4
 group B, 7-15
 flooring, 14-5
 pavers, 14-4
 group C, 7-15 to 7-16
 furniture and tops, 19-1
 group D, 7-16
 furniture and tops, 19-1
 hardness and flooring, 7-18
 honed finish, 7-3
 honing powders, 21-36
 hysteresis, 7-19 to 7-20, 7-21
 Iceland Spar, 7-11
 installation, 7-5 to 7-7
 curing compounds, 7-5
 tamping, 7-5
 thin-set method, 7-6
 insulating materials, 7-18
 interior veneer, 7-6
 Italian, 7-10
 liquid polishes, 21-36
 magnesite, 7-10
 marble blocks, 7-15
 marble, composition of, 7-8 to 7-13
 microfractures, 7-12
 modulus of elasticity, 7-17
 modulus of rupture, 7-17, 24-4
 moldings, 7-4
 mortar, 7-3
 mortar setting of, 7-5 to 7-6
 onyx
 color, 7-13
 composition of, 7-13
 geological origin, 7-13
 travertine and, 7-13, 12-8 n1
 "orange peel", 21-13
 packing and loading, 7-5
 panel thickness, 7-4
 pavers, 14-4
 physical properties, 7-16 to 7-17, 24-4
 polished finish, 7-3
 polishing pastes, 21-36
 polishing powders
 characteristics of, 21-35 to 21-36
 defined, 21-34 to 21-35
 primary depositional features, 7-9
 protection of, 7-7 to 7-8
 pyrite, 7-10
 quarry blocks, 7-14 to 7-15
 quarter match pattern, 7-D.3
 repairing, 21-13 to 21-14
 Rosso, 21-14
 Rosso Levanto, 21-15
 sampling, 7-14
 sealant joints, 7-7
 sealants, 7-3
 seismic considerations, 7-18, 7-20
 shims, 7-4
 side slip pattern, 7-D.2
 sizes, 7-14
 soundness classification, 7-15 to 7-16
 squareness, 7-16
 staining, 7-19, 7-20 to 7-21
 stair treads, 14-13
 storage, 7-5
 strength, 7-17
 stylolites, 7-9 to 7-10
 Tennessee Pink, 21-14
 texture, 7-13
 thermal conductivity, 7-17
 thermal expansion, 7-20, 7-21
 thickness, 7-14, 7-16
 thresholds, 14-11
 toilet and shower
 compartments, 7-6
 translucence, 7-20, 7-21
 usage tips, 7-14
 variegated types, 21-14
 vein cut, 7-16
 veining, 7-14
 veneer cutting, 7-14 to 7-15, 7-D.1
 veneer patterns, 7-D.2 to 7-D.3
 voids, 7-9, 7-10 to 7-11
 vugs, 7-10 to 7-11
 wall tile, 7-6
 washes, 7-4
 water absorption, 7-18, 24-4
 water vapor permeability, 7-17
 weathering, 7-18
 weep tubes, 7-7
 white Carrara, 21-13
 white marble
 defined, 21-13
 effective techniques, 21-13
 wind loads, 7-18
 window stools, 18-3
 wire anchors, 7-4
 marble blocks, 7-15
 Marble Institute of America (MIA),
 defined, 23-16
 masonry, defined, 23-16
 masonry backup for interior cladding, 14-14
 masonry cement
 limestone, 6-3
 travertine, 12-3
 masonry construction and window stools, 18-D.2
 masonry fireplace, 14-D.19 to 14-D.20
 matched stone samples, 3-7
 matched-vein patterns, 3-3
 Material Safety Data Sheet (MSDS), defined, 23-17
 mechanical repairs, 21-8
 mechanical systems, anchors, 14-14 to 14-15, 21-18
 membranes, 13-7
 pavers, 14-3 to 14-4
 metaconglomerates, 8-7, 8-9
 metal backup for exterior stone veneer, 14-D.3
 metal edges, 13-11
 metal frame for sink hole, 17-D.10
 metal studs
 interior cladding, 14-14 to 14-15, 14-D.10
 exterior stone veneer, 14-D.2, 14-D.5
 metamorphic, defined, 21-1
 metamorphic rock, 1-2
 cleaning and maintenance, 21-78
 defined, 23-16
 geological classification, 21-70
 metamorphic stone, 1-6 to 1-7
 metaquartzite, 8-8
 metamorphism, defined, 23-16
 metaquartzite, 8-7, 8-8
 mica, hardness, 21-2
 microcrystalline, defined, 23-16
 milling, defined, 23-16
 miter
 defined, 23-16
 quirk miter, 23-21, 22-D-App B
 miter joint, countertops, 17-D.3
 mixing tools, 21-43
 mixing types of stone, 3-3
 mockups, 3-6, 5-2, 6-2, 7-2, 8-2, 9-2, 10-2, 12-2, 14-3
 defined, 23-16
 horizontal applications, 13-1
 soapstone, 11-2
 testing of, 20-1
 moderate foot-traffic, 13-4
 interior, 3-5

- modular, defined, 23-16
 - modular stone tiles, 3-3, 3-7 to 3-8
 - modulus of elasticity
 - defined, 23-16
 - granite, 5-11
 - limestone, 6-12
 - marble and onyx, 7-17
 - precast concrete panels, 20-1
 - quartz-based stone, 8-11
 - serpentine, 9-13
 - stone veneer panels, 20-1
 - travertine, 12-12
 - modulus of rupture, 4-6
 - See also* flexural strength
 - defined, 23-16
 - granite, 5-11
 - limestone, 6-12
 - marble and onyx, 7-17
 - quartz-based stone, 8-11
 - serpentine, 9-13
 - slate, 10-11
 - travertine, 12-12
 - Mohs scale, 5-9, 17-10, 17-12, 24-2
 - defined, 21-2, 23-16
 - moisture, flooring, 14-7
 - moisture penetration, 13-18
 - steam rooms and showers, 16-8
 - moisture proofing, steam rooms and showers, 16-12
 - moisture sensitivity, 13-18
 - mold and mildew
 - cementitious backer units, 16-2
 - drywall, 16-2
 - molded joint, *14-D.16*
 - moldings
 - defined, 23-16
 - granite, 5-4
 - limestone, 6-4
 - marble and onyx, 7-4
 - quartz-based stone, 8-3
 - serpentine, 9-4
 - slate, 10-3 to 10-4
 - soapstone, 11-3
 - travertine, 12-4
 - monolithic, defined, 23-16
 - mortar
 - defined, 23-17
 - dry-pack, 13-8
 - dry-set, 13-8 to 13-9
 - pointing mortar, slate, 10-3
 - setting mortar, slate, 10-3
 - setting of stone, travertine, 12-5 to 12-6
 - thin-set, 13-8 to 13-9
 - mortar bed, *13-D.3*
 - bond coat, *13-D.1*
 - bonded to subfloor, 13-14 to 13-15
 - concrete subsurface bonding, 13-11 to 13-12
 - expansion joint, *13-D.1*
 - flooring, 14-8
 - heated floor systems, 13-17
 - limestone setting, 14-7
 - membrane, *13-D.1*
 - movement joint, *13-D.1*
 - portland cement, 14-6
 - reinforcement, 14-5
 - reinforcement, 14-6
 - separate from subfloor, 13-15 to 13-16
 - thin bed, 13-15 to 13-16
 - thin-set, *13-D.1*, *13-D.3*, 14-6 to 14-7
 - wood frame subfloor, *13-D.3*
 - wood subfloor, *13-D.3*
 - mortar bed weight, 13-5
 - joints
 - granite, 5-5
 - limestone, 6-6, 8-5
 - marble and onyx, 7-6
 - serpentine, 9-7
 - pointing mortar
 - granite, 5-3
 - limestone, 6-3
 - marble, 7-3
 - onyx, 7-3
 - quartz-based stone, 8-3
 - serpentine, 9-4
 - setting mortar
 - granite, 5-3
 - limestone, 6-3
 - marble, 7-3
 - onyx, 7-3
 - quartz-based stone, 8-3
 - serpentine, 9-3 to 9-4
 - setting of stone
 - granite, 5-5
 - limestone, 6-6
 - marble and onyx, 7-5 to 7-6
 - quartz-based stone, 8-5
 - serpentine, 9-6
 - mortar joints
 - slate, 10-5
 - travertine, 12-6
 - mosaic, defined, 23-17
 - movement joints, 13-6, 14-9
 - defined, 23-16
 - exterior pavers, 14-5
 - pavers, 14-2
 - MSDS (Material Safety Data Sheet), defined, 23-17
 - MTL (marble/travertine/limestone)
 - See also* marble and onyx;
 - limestone; travertine
 - consistent MTL group
 - Crema Marfil, 21-11 to 21-12
 - defined, 21-11
 - effective techniques, 21-12
 - general notes, 21-13
 - consistent variegated MTL group
 - Botticino, 21-14
 - defined, 21-14
 - effective techniques, 21-14
 - edging, 21-54
 - lippage removal, 21-53, 21-54
 - polishing, frankfurt, 21-30
 - refinishing and polishing
 - edging, 21-54
 - first grinding, 21-54 to 21-55
 - honing, 21-56 to 21-57
 - initial honing, 21-56
 - light grinding, 21-55 to 21-56
 - lippage removal, 21-53, 21-54
 - other finishes, 21-58
 - polishing, 21-57 to 21-58
 - preparation, 21-53 to 21-54
 - refinishing, 21-55
 - sealing, 21-58
 - variegated MTL group, 21-14
 - mudstone, 1-5
 - mullion, defined, 23-17
- ## N
- National Building Granite Quarries Association (NBGQA)
 - defined, 23-17
 - publications, 5-2
 - National Building Museum, v
 - National Sanitation Foundation, *See* NSF International
 - National Tile Contractors Association (NTCA), defined, 23-17
 - natural bed, defined, 23-17
 - natural cleft, defined, 23-17
 - natural cleft finish, 3-2, 19-2
 - slate, 10-9
 - natural stone, defined, 23-17
 - Natural Stone Institute (NSI), i
 - defined, 23-17
 - code of ethics, xiv
 - membership, xv
 - publications, 3-8, 4-10
 - statement of position on sealers, 3-5 to 3-6
 - NBGQA
 - defined, 23-17

publications, 5-2
neat cement, 5-7
 See also back parging; parge
 defined, 23-17
negative flow, defined, 16-2
Neolite, 4-9
neutral cleaners, 21-84
niche, defined, 23-17
NIOSH (National Institute for
Occupational Safety and Health),
defined, 23-17
noise restrictions, 21-26
nonferrous anchors, cramps, and
dowels, 8-3
nonstaining mortar, defined, 23-17
nonstick mastic compound, 10-5
Normandy edge, 17-D.16, 19-D.3
notch, defined, 23-17
NSF International, 2-3 to 2.4
NSF Material Requirements
(Standard 51), 2-3 to 2.4
NSF/ANSI standards, 2-6
NSI (Natural Stone Institute), i
 defined, 23-17
 code of ethics, xiv
 membership, xv
 publications, 3-8, 4-10
 statement of position on sealers,
 3-5 to 3-6
NTCA (National Tile Contractors
Association), defined, 23-17

O

obsidian, defined, 23-17
occupants' access, commercial and
historical restoration, 21-86
Occupational Safety and Health
Administration (OSHA), defined,
23-18
oceanic stone, 1-2 to 1-3
off fall. *See* remnant (23-21)
Office of the Federal
Environmental Executive, v
offset butt joint, 14-D.9
ogee, defined, 23-17
ogee edge, 17-D.16, 19-D.3
ogee roundover edge, 17-D.16, 19-
D.3
oil-based putty
 cubic sills, 18-3, 18-4
 exterior cubic stone coping and
 walls, 18-1, 18-2
 furniture and tops, 19-1, 19-2
 wet areas, 16-1
 window stools, 18-3, 18-4
onyx, 7-13
 countertops, 17-1

 defined, 23-18
 geological classification, 21-70
oolitic limestone, defined, 23-18
open-faced quarry, defined, 23-18
organization websites, iv
orthoclase, hardness, 21-2
orthoquartzite vs. granite, 5-9
OSHA (Occupational Safety and
Health Administration), defined,
23-18
out-crop, defined, 23-18
outriggers, defined, 23-18
outward crack, repairs, 21-44
overburden, defined, 23-18
overhangs, 23-6
 defined, 23-18
 furniture and tops, 19-1
 thickness, 19-1
oxalic acid, 21-13
 defined, 23-18
 polishing powders, 21-35

P

palletize, defined, 23-18
pan, steel for stair treads, 13-D.6,
13-D.8
panel, defined, 23-18
panel deformation, 21-19
panels
 precast concrete, 20-D.1 to 20-
 D.2
 coefficient of thermal
 expansion, 20-1
 color, 20-1
 compressive strength, 20-1
 finishes, 20-1
 installation, 20-2
 limitations, 20-1
 modulus of elasticity, 20-1
 physical properties, 20-1
 shear strength, 20-1
 sizes, 20-1
 tensile strength, 20-1
 testing mockups, 20-1
 thickness, 20-1
 showers, residential, 16-8
parallel vs. perpendicular testing, 4-
3
parapet, defined, 23-18
parapet details for exterior cubic
stone coping and walls, 18-D.1
parge. *See also* back parging; neat
cement
 defined, 23-18
particle names (clast sizes), 1-5
patching materials, 21-39
 acrylics, 21-40 to 21-41
 cyanoacrylate (CA) glues, 21-
 41 to 21-42
 epoxy, 21-41
 general notes, 21-42
 hybrids, 21-42
 polyester resins, 21-40
 urethane, 21-41
patina, defined, 23-18
patterned and matched panels, 3-3
pavers
 coefficient of friction (COF),
 14-3
 defined, 23-18
 dry-pack mortar, 13-12 to 13-13
 finishes, 13-3
 granular bed method, 13-14
 hollow sound, 14-1 to 14-2
 installation methods, 13-17
 joint width, 13-5, 14-2
 lippage, 14-3
 membranes, 14-3 to 14-4
 pedestal systems, 13-13, 13-D.2
 sand installation, 13-D.2
 thickness, 14-2 to 14-3
 underlayment limitations, 13-5
paving, defined, 23-18
pebble, clast size, 1-5
pebble conglomerate, 1-5
pedestal, 23-7, 23-9, 23-19
 defined, 23-18
pedestal system and exterior
pavers, 13-13, 13-D.2, 14-6
pediment, defined, 23-18
PEL (permissible exposure limit),
defined, 23-18
pencil round edge, 17-D.16, 19-D.3
percussion drilling, defined, 23-19
perforated wall, defined, 23-19
pergola, defined, 23-19
perimeter joints, defined, 21-19
permeability, sealers, 21-69
permissible exposure limit (PEL),
defined, 23-18
personal protective equipment
(PPE)
 defined, 23-19 to 23-20
 for repairs, 21-40, 21-43, 21-45
petrography, 4-1
pH, 21-3
 cleaners, 21-36 to 21-37
phenocryst, defined, 23-19
phyllite, 5-9, 10-7 to 10-8
picked, hand-hewn, rock face
finish, 3-2
picture framing, 21-32, 21-55
pilaster, defined, 23-19
pillowed, defined, 23-19
pit quarry, defined, 23-19

- pitch faced finish, 5-7
 - defined, 23-19
 - pitched stone (pitch faced), defined, 23-19
 - pits, 21-23
 - pitting of granite, 5-14, 17-12
 - planed finish, 3-2
 - slate, 10-9
 - plastic lime hydrate
 - quartz-based stone, 8-3
 - slate, 10-3
 - plastic setting pads
 - limestone installation, 6-6
 - travertine installation, 12-6
 - plate tectonics, 1-3 to 1-4
 - platner edge, *17-D.16, 19-D.3*
 - plinth, *23-7, 23-9, 23-18*
 - defined, 23-19
 - plucked finish
 - defined, 23-19
 - limestone, 6-10
 - travertine, 12-7
 - plug anchors, *14-D.24*
 - plumbing sealants, wet areas, 16-1
 - plutonic, defined, 23-19
 - plywood subfloors, 13-11, 14-10
 - mortar bed, *13-D.3*
 - plywood subtops, 19-1
 - pointed finish. *See* bush-hammered finish
 - pointing, defined, 23-19
 - polished finish, 3-2, 19-2
 - countertops, 17-2
 - defined, 21-5, 21-75, 23-19
 - granite, 5-6
 - limestone, 6-10
 - marble and onyx, 7-3, 7-14
 - serpentine, 9-12
 - travertine, 12-7, 12-10
 - polishing
 - defined, 23-19
 - granite countertops, 21-64
 - granite refinishing and polishing, 21-61
 - MTL refinishing and polishing, 21-57 to 21-58
 - polishing compounds, defined, 23-19
 - polishing cream, defined, 23-19
 - polishing pads
 - defined, 23-19
 - miscellaneous, 21-36
 - types of, 21-35 to 21-36
 - polishing powders
 - bricks, 21-30
 - characteristics of, 21-35
 - marble, 21-34 to 21-35
 - polishing pastes, 21-36
 - time, 21-36
 - polishing tools, 21-43
 - right-angle polisher, 21-47
 - polishing wheel marks, 13-19, 14-17
 - poly-epoxy, properties, 21-49
 - polyester, properties, 21-49
 - polyester-based resin adhesives, 21-8
 - polyester resin, 17-9, 17-10
 - pool environments, diagnostic considerations, 21-24
 - porosity of stone and exterior applications, 3-4
 - porous limestone
 - defined, 21-12
 - effective techniques, 21-12
 - porphyry, defined, 23-19
 - portico, defined, 23-19
 - portland cement, 14-6
 - light colored stones, 14-7
 - portland cement mortar, 13-8, 13-16
 - positive flow, defined, 16-2
 - poultices, 21-52
 - defined, 23-19
 - for stains, 21-82 to 21-83
 - PPE (personal protective equipment)
 - defined, 23-19 to 23-20
 - for repairs, 21-40, 21-43, 21-45
 - preassembled units, defined, 23-20
 - precast, defined, 23-20
 - preparation
 - exterior cubic stone coping and walls, 18-2
 - showers, residential, 16-8, 16-11
 - steam rooms and showers, 16-9
 - pressure relieving joints, *14-D.6*
 - pressure washing, 21-84
 - pricing stone, 3-7 to 3-8
 - primer, defined, 23-20
 - privacy partition
 - See also* urinal screens
 - defined, 23-20
 - producer, defined, 23-20
 - profile wheel, defined, 23-20
 - project samples, 3-6
 - projections, defined, 23-20
 - promotional samples, color consideration, 3-6
 - prospecting, defined, 23-20
 - protection of stone
 - finished work, 13-17 to 13-18
 - granite, 5-6 to 5-8
 - limestone, 6-8
 - marble and onyx, 7-7 to 7-8
 - quartz-based stone, 8-6
 - serpentine, 9-8
 - slate, 10-6
 - soapstone, 11-4
 - travertine, 12-7
 - pumice, defined, 23-20
 - pyrite, 7-10
 - pyroxene, 11-5
- ## Q
- quarried stone, defined, 23-20
 - quarrier, defined, 23-20
 - quarry, defined, 23-20
 - quarry block
 - defined, 23-20
 - marble and onyx, 7-14 to 7-15
 - quarry run, defined, 23-20
 - quarry sap, defined, 23-20
 - quarrying, x
 - quarter match pattern, *7-D.3*
 - quarter-point loading and flexural strength test, 4-7
 - quartz
 - composition of, 8-7
 - defined, 23-20
 - granite, 5-9
 - hardness, 17-10, 17-12, 21-2
 - quartz-based stone
 - abrasion resistance, 8-12, 24-4
 - absorption of stone, 8-11, 24-4
 - anchorage, 8-5 to 8-6
 - anchors, wire, 8-3
 - back-checking, 8-4
 - backs of pieces, 8-3
 - bolted connections, back-checking, 8-3
 - caulking, 8-6
 - cleaning, 8-6
 - color, 8-9
 - compressive strength, 8-11, 24-4
 - cramps, 8-3
 - crystalline quartz, 8-7 to 8-8
 - damaged stone, repairing, 8-2
 - defined, 23-20
 - density, 8-11, 24-4
 - dowels, 8-3
 - drips, 8-3
 - efflorescence, 8-13 to 8-14
 - expansion joints, 8-6
 - fabrication, 8-11
 - finishes, 8-10
 - fire resistance, 8-12
 - flexural strength, 8-11, 24-4
 - geological classification, 8-6 to 8-9
 - hardness and flooring, 8-12

- installation, 8-5 to 8-6
 - main groups of, 8-7
 - modulus of elasticity, 8-11
 - modulus of rupture, 8-11, 24-4
 - moldings, 8-3
 - mortar, 8-3, 8-5
 - packing and loading, 8-4
 - physical properties, 8-11 to 8-12, 24-4
 - plastic lime hydrate, 8-3
 - protection of, 8-6
 - safety factors, 8-12 to 8-13
 - sampling, 8-1 to 8-2, 8-10
 - sealant joints, 8-6
 - sealants, 8-3
 - seismic considerations, 8-13
 - seismic loads, 8-13
 - sizes, 8-10
 - staining, 8-13 to 8-14
 - storage, 8-4
 - strength, 8-12
 - tensile strength and thickness, 8-10
 - texture, 8-9 to 8-10
 - thermal expansion, 8-14
 - thickness, 8-10
 - thin wall tile, 8-5
 - tolerances, 8-10
 - usage tips, 8-10
 - vener, 8-5
 - washes, 8-3
 - water absorption, 24-4
 - weep tubes, 8-6
 - wind loads, 8-13
 - quartz pebble conglomerates, 8-7, 8-8 to 8-9
 - quartz sandstone, 1-5 n10
 - quartzite, 8-7, 8-8, 23-21
 - abrasion resistance, 24-4
 - absorption of stone, 24-4
 - compressive strength, 24-4
 - defined, 21-15
 - density, 24-4
 - effective techniques, 21-15 to 21-16
 - flexural strength, 24-4
 - geological classification, 21-70
 - granite vs., 5-9
 - hardness for flooring, 8-12
 - identification, 21-15
 - modulus of rupture, 24-4
 - physical properties, 24-4
 - water absorption, 24-4
 - quartzitic sandstone
 - abrasion resistance, 24-4
 - absorption of stone, 24-4
 - compressive strength, 24-4
 - defined, 23-21
 - density, 24-4
 - flexural strength, 24-4
 - hardness for flooring, 8-12
 - modulus of rupture, 24-4
 - physical properties, 24-4
 - water absorption, 24-4
 - quirk joint, *14-D.9*
 - quirk miter joint, *14-D.9, 14-D.16*
 - quirk miters, 19-1
 - defined, 23-21
 - tolerances, *22-D-App B*
 - quoin, defined, 23-21
- R**
- rabbit, defined, 23-21
 - rabbeted joint, *14-D.9, 14-D.16*
 - radius edges, *17-D.16, 19-D.3*
 - undermount sink support, *17-D.8*
 - radius of rounded edges, 19-1
 - radon, granite, 5-14
 - rain screen, defined, 23-21
 - raked joint, defined, 23-21
 - random ashlar, 23-3
 - random slab, defined, 23-21
 - rebated kerf, defined, 23-21
 - recess, defined, 23-21
 - recrystallization. *See* crystallization
 - recrystallized limestone, defined, 23-21
 - refinishing
 - Crema Marfil, 21-11
 - defined, 23-21
 - Noce Travertine, 21-11
 - reglets
 - defined, 23-21
 - exterior stone veneer, *14-D.9*
 - flashing, 6-4
 - limestone, 6-4
 - reinforcement, defined, 23-21
 - reinforcement techniques for countertops, 17-11
 - reinforcements, identification, 21-7 to 21-9
 - relief, defined, 23-21
 - relief angle connection, *14-D.4*
 - relieving angle-clip, *14-D.24*
 - relieving arch, defined, 23-21
 - remnant, defined, 23-21
 - repairing damaged stone
 - countertops, 17-11 to 17-12
 - granite, 5-3
 - limestone, 6-2
 - marble, 7-2
 - onyx, 7-2
 - quartz-based stone, 8-2
 - serpentine (during fabrication), 9-2
 - slate, 10-2
 - soapstone, 11-2
 - sticking, 9-2
 - travertine, 12-2
 - repairs
 - adhesives, consistency, 21-45
 - chips, 21-44
 - color matching, 21-46
 - damage types, 21-43
 - downward crack, 21-44
 - finishing, 21-46
 - identification, 21-7 to 21-9
 - inspection, 21-43
 - inward crack, 21-44
 - macro-cracks, 21-45 to 21-46
 - maintenance, 21-76
 - micro-cracks, 21-45
 - outward crack, 21-44
 - preparation, 21-45
 - seams or cracks, 21-48
 - suggestions, 21-44
 - upward crack, 21-43
 - reprise, defined, 23-21
 - resin, defined, 23-21
 - resin-impregnated slabs, 17-11
 - resin impregnation, 21-7
 - resin patching sticks, defined, 23-22
 - resin polishing, defined, 23-22
 - resined slab, defined, 23-22
 - resort environments, diagnostic considerations, 21-24
 - resources
 - mechanical anchors, 21-18
 - tile, 21-18
 - restoration
 - additional resources, 21-121
 - budgetary concerns, 21-72
 - defined, 21-51, 21-75, 23-22
 - masking and protecting, 21-52 to 21-53
 - previous restoration, 21-21
 - surface preparation, 21-51
 - restraint anchorage, *14-D.7*
 - expansion bolts, *14-D.8*
 - exterior stone veneer, *14-D.7*
 - interior stone veneer, *14-D.8*
 - return, defined, 23-22
 - return head, defined, 23-13
 - reveal
 - defined, 23-22
 - free-standing column, *14-D.14*
 - ribbons, 10-8
 - defined, 23-22
 - rift
 - defined, 23-22
 - testing in relation to direction

- of, 4-3
 - rigidity, 21-19
 - riprap, defined, 23-22
 - riser, 23-25, 23-27
 - rock
 - defined, 23-22
 - vs. stone, 1-1
 - rock cycle, 1-7, 1-8
 - rock-faced finish
 - defined, 23-22
 - granite, 5-7
 - marble and onyx, 7-14
 - rocked edge, 17-D.16, 19-D.3
 - rodding, 21-8
 - See also* reinforcement
 - countertops, 17-11, 17-D.5
 - defined, 23-22
 - Roman arch, defined, 23-22
 - rosette detail, interior cladding, 14-D.15
 - rosette fasteners, interior cladding, 14-D.15
 - rough back, defined, 23-22
 - rough finish, 19-2
 - rough sawn finish
 - defined, 23-22
 - exterior cubic stone coping and walls, 18-1
 - marble and onyx, 7-14
 - rubbed finish, 5-7
 - defined, 23-22
 - rubber bristle brushes, 21-37
 - rubble, defined, 23-22
 - rustication, defined, 23-23
- S**
- saddle (threshold), defined, 23-26
 - safety factors
 - compressive loads, 4-5
 - quartz-based stone, 8-12 to 8-13
 - seismic loads
 - granite, 5-13
 - limestone, 6-14
 - quartz-based stone, 8-13
 - travertine, 12-13 to 12-14
 - wind loads
 - granite, 5-13
 - limestone, 6-14
 - marble and onyx, 7-18
 - quartz-based stone, 8-13
 - serpentine, 9-14 to 9-15
 - slate, 10-12
 - travertine, 12-13 to 12-14
 - salt
 - granite, 5-7
 - limestone, 6-5
 - marble and onyx, 7-5
 - quartz-based stone, 8-5
 - serpentine, 9-5
 - slate, 10-5
 - soapstone, 11-4
 - travertine, 12-5
 - salt attack, 21-4
 - saltwater environments, 21-24
 - sample specification language, xvii to xviii
 - samples, 14-3
 - defined, 23-23
 - granite, 5-2
 - horizontal applications, 13-1
 - limestone, 6-1 to 6-2
 - marble, 7-1 to 7-2
 - onyx, 7-1 to 7-2
 - quartz-based stone, 8-1 to 8-2
 - serpentine, 9-1 to 9-2
 - slate, 10-1 to 10-2
 - soapstone, 11-1 to 11-2
 - travertine, 12-1 to 12-2
 - sampling, 3-6 to 3-7
 - granite, 5-10
 - large projects, 3-6 to 3-7
 - limestone, 6-11
 - marble and onyx, 7-14
 - number, 3-6 to 3-7
 - quartz-based stone, 8-10
 - serpentine, 9-12
 - slate, 10-9
 - travertine, 12-10 to 12-11
 - sand
 - clast size, 1-5
 - grout, 14-7
 - limestone, 6-3
 - marble, 7-3
 - onyx, 7-3
 - portland cement mortar, 14-6
 - travertine, 12-3
 - sand bed installation, 13-D.2, 14-6
 - sand grain composition, 1-5
 - sand rubbed finish, 10-9
 - sandblasted finish, 3-2
 - defined, 23-23
 - granite, 5-7
 - slate, 10-9
 - sandblasting, 21-84
 - sanded finish, defined, 21-6
 - sandstone, 1-5, 8-7, 8-8
 - See also* quartz-based stone
 - abrasion resistance, 24-4
 - absorption of stone, 24-4
 - compressive strength, 24-4
 - defined, 21-16, 23-23
 - density, 24-4
 - effective techniques, 21-16
 - flexural strength, 24-4
 - geological classification, 21-70
 - hardness for flooring, 8-12
 - modulus of rupture, 24-4
 - physical properties, 24-4
 - texture, 8-10
 - water absorption, 24-4
 - sawed edge, defined, 23-23
 - sawed face, defined, 23-23
 - sawing countertops, 17-5
 - sawn finish, 3-2
 - granite, 5-7
 - limestone, 6-10
 - travertine, 12-10
 - sawyer, defined, 23-23
 - scabbing (dressing), defined, 23-9
 - scaling, travertine, 12-14
 - schist, 5-9, 9-9, 9-11, 10-8
 - defined, 23-23
 - scotia, defined, 23-23
 - scratches, 21-23
 - pressure scratches, 21-23
 - removal of, 21-23
 - screed, defined, 23-23
 - sculpture, defined, 23-23
 - sea-floor spreading, 1-3
 - sealant joints
 - granite, 5-6
 - limestone, 6-7
 - marble and onyx, 7-7
 - quartz-based stone, 8-6
 - serpentine, 9-8
 - slate, 10-6
 - travertine, 12-6
 - sealants
 - backer rods, 14-9
 - cubic sills, 18-3, 18-4
 - defined, 23-23
 - fungicide, 14-8
 - furniture and tops, 19-1, 19-2
 - granite, 5-3
 - joint sealants, 14-8 to 14-9
 - limestone, 6-3
 - marble, 7-3
 - oil-based organic, 14-8
 - onyx, 7-3
 - primers, 5-6, 6-7, 7-7, 8-6, 9-8, 10-6, 11-4, 12-6, 14-8
 - quartz-based stone, 8-3
 - serpentine, 9-4
 - silicone, 13-10, 14-8
 - slate, 10-3
 - soapstone, 11-4
 - staining, 13-19, 14-8 to 14-9, 14-16 to 14-17
 - surface sealers, 14-10
 - travertine, 12-3
 - urethane, 13-10
 - window stools, 18-3, 18-4
 - sealers

actives, 21-68
 appropriateness, 21-69 to 21-70
 carriers, 21-68
 coatings, 21-67 to 21-68
 color-enhancing impregnators, 21-67
 commercial clients, 21-71 to 21-72
 countertops, 17-6, 17-12
 defined, 21-6, 23-23
 exteriors, 21-70 to 21-71
 field tests, 21-72 to 21-74
 film-forming sealers, 21-23, 21-67 to 21-68
 finished appearance, 21-71
 flooring, 14-7
 fluoropolymers, 21-68
 general characteristics, 21-68 to 21-69
 granite, 21-61, 21-64
 impregnating repellents, 21-67
 impregnating sealers, 21-80
 introduction, 21-67
 maintenance, 3-8, 21-71, 21-72
 MIA statement, 3-5 to 3-6
 penetrating sealers, 3-5, 21-67
 performance expectations, 21-71
 points to remember, 21-74
 residential and commercial interiors, 21-70
 residential clients, 21-71
 resin-impregnated slabs, 17-11
 sealer components, 21-68
 sealer selection, 21-72
 silicone-based chemicals, 21-68
 solvent-based coatings, 21-68
 staining, 21-70
 Standard 51, 2-4
 timing, 21-80
 topical sealers, 17-12, 21-23, 21-80
 VOC tolerance, 21-72
 water-based carriers, 21-68
 sealing
 defined, 23-23
 furniture and tops, 19-1
 MTL refinishing and polishing, 21-58
 seam filler material for countertops, 17-7, 17-9, 17-13
 seam setter
 countertop repair, 21-46
 defined, 23-23
 seam width, countertops, 17-6
 seams, granite, 21-48
 sedimentary, defined, 21-1, 23-24
 sedimentary rock, 1-1 to 1-2
 geological classification, 21-70
 sedimentary stone, clastic, 1-4 to 1-5
 seismic considerations
 granite, 5-13
 marble and onyx, 7-18, 7-20
 quartz-based stone, 8-13
 serpentine, 9-15
 slate, 10-12
 travertine, 12-14
 self-leveling underlayment for stone tiles, 13-5
 serpentine
 See also MTL
 (marble/travertine/limestone)
 abrasion resistance, 9-13, 9-14, 24-4
 absorption of stone, 9-13, 24-4
 adhesive, 9-4, 13-18 to 13-19
 anchorage, 9-7
 anchors, 9-4
 asbestos content, 9-3
 back-checking, 9-4
 backs of pieces, 9-4
 bolted connections, back-checking, 9-4
 carving, 9-5
 caulking, 9-8
 cleaning, 9-8
 color, 9-11 to 9-12
 composition of, 9-9
 compressive strength, 9-13, 24-4
 countertops, 17-1
 cramps, 9-4
 damaged stone, repairing during fabrication, 9-2
 damaged stone, repairing during installation, 9-3
 defined, 21-15, 23-24
 density, 9-13, 24-4
 dowels, 9-4
 drips, 9-4
 effective techniques, 21-15
 efflorescence, 9-15 to 9-16
 expansion joints, 9-8
 finishes, 9-3, 9-12
 fire resistance, 9-15
 fleuri cut, 9-13
 flexural strength, 9-13, 24-4
 floor installation, 9-6 to 9-7
 flooring, 9-13 to 9-14
 geological classification, 9-8 to 9-11, 21-70
 gypsum molding plaster, 9-7
 hardness, 9-9, 9-14, 21-15
 installation, 9-5 to 9-8
 insulator, 9-14
 interior veneer, 9-7
 limitations, 9-11
 marble and, 9-8 to 9-9
 modulus of elasticity, 9-13
 modulus of rupture, 9-13, 24-4
 Mohs scale, 21-15
 moldings, 9-4
 mortar, 9-3 to 9-4
 mortar setting of, 9-6
 packing and loading, 9-5
 physical properties, 24-4
 protection of, 9-8
 safety factor, 9-14 to 9-15
 sampling, 9-12
 sand, 9-6
 sealant joints, 9-7
 sealants, 9-4
 seismic considerations, 9-15
 setting beds and water, 9-6
 sizes, 9-12
 staining, 9-16
 storage, 9-5
 strength, 9-14
 texture, 9-12
 thickness, 9-12
 toilet and shower compartments, 9-7
 usage tips, 9-13 to 9-14
 vein-cut, 9-13
 veining, 9-11 to 9-12
 veneer cutting, 9-13
 vertical surfaces, 14-16
 wall tile, 9-7
 washes, 9-4
 water absorption, 9-14, 24-4
 water and installation, 9-6
 weathering, 9-14
 weep tubes, 9-8
 wind loads, 9-14 to 9-15
 setter, defined, 23-24
 setting, defined, 23-24
 setting beds, stair treads, *13-D.6* to *13-D.8*
 setting space, defined, 23-24
 shading variation in stone tile countertops, 17-9
 shale, 1-5
 defined, 23-24
 shear, defined, 23-24
 shear strength
 precast concrete panels, 20-1
 stone veneer panels, 20-1
 sheet applied bonded membrane, defined, 16-2
 shellac, polishing powders, 21-35
 shelves, *17-D.14*
 shims, 14-9 to 14-10, *14-D.23*
 countertops, 17-5

- repair, 21-46
- defined, 23-24
- interior stone base, *14-D.17*
- plastic, *14-D.23*
 - marble, 7-4
 - onyx, 7-4
- slate and, 10-5
- stainless steel, *14-D.23*
- shop drawings
 - countertops, 17-3
 - defined, 23-24
 - granite, 5-2 to 5-3
 - horizontal applications, 13-2
 - kitchen layouts and countertops, *17-D.17*
 - limestone, 6-2
 - marble, 7-2
 - onyx, 7-2
 - quartz-based stone, 8-2
 - serpentine, 9-2
 - slate, 10-2
 - soapstone, 11-2
 - travertine, 12-2
- shop ticket, defined, 23-24
- shot ground finish, 5-7
- shot sawed, defined, 23-24
- shower pan, defined, 16-2
- shower partitions
 - color, 16-5
 - details, *16-D.5*
 - elevations, *16-D.4*
 - fabrication, 16-5
 - finishes, 16-5
 - floor-mounted, 16-6
 - free-standing units, 16-6
 - installation, 16-5 to 16-6
 - sizes, 16-5
 - soundness, 16-5
 - types, 16-5
 - waterproof pan receptor types, *16-D.4*
- shower receptors, *16-D.4*
- showers, residential
 - color, 16-8, 16-10
 - details, *16-D.8*
 - elevations, *16-D.6* to *16-D.7*
 - stone slab
 - anchors, 16-8
 - exposed edges, 16-8
 - fabrication, 16-7
 - installation, 16-8
 - joint width, 16-7 to 16-8
 - panels, 16-8
 - polished finish, 16-8
 - preparation, 16-8
 - sizes, 16-7
 - soundness, 16-7
 - stone ceiling, 16-8
- stone tile
 - details, *16-D.10*
 - elevations, *16-D.9*
 - exposed edges, 16-10
 - fabrication, 16-10
 - installation, 16-10 to 16-11
 - joint width, 16-11
 - polished finish, 16-10
 - preparation, 16-10 to 16-11
 - sizes, 16-10
 - soundness, 16-10
 - thickness, 16-10
- side slip pattern, *7-D.2*
- siderite, 6-8, 9-10 to 9-11
- sidesplashes, *17-D.13*
- silica
 - cementing material, 1-5
 - defined, 23-24
- silicates, 1-1
- siliceous, defined, 23-24
- siliceous stones
 - acid attack, 21-3 to 21-4
 - defined, 21-2
 - sealers, 21-70
- sill, defined, 23-24
- silt, clast size, 1-5
- siltstone, 1-5
 - defined, 23-24
- simulated stone, defined, 23-24
- sink flange, *17-D.8*
- sink mounts, 17-4
- sinks
 - cast-iron, 17-3
 - support details, *17-D.8* to 17-10
- site access, commercial and historical restoration, 21-86
- sizes
 - cubic sills, 18-3
 - exterior pavers, 14-5
 - furniture and tops, 19-2
 - granite, 5-10
 - limestone, 6-11
 - marble and onyx, 7-14
 - precast concrete panels, 20-1
 - quartz-based stone, 8-10
 - serpentine, 9-12
 - shower partitions, 16-5
 - showers, residential, 16-10
 - slate, 10-9
 - stair treads, 14-14
 - steam rooms and showers, 16-10
 - stone veneer panels, 20-1
 - thresholds, 14-11
 - toilet partitions, 16-3
 - travertine, 12-10
 - urinal partitions, 16-4
 - window stools, 18-3
- slab, defined, 23-24 to 23-25
- slab production table, 24-2
- slab stock, 13-1
 - defined, 14-1
- slab warp, allowable lippage, *17-7*
- slate
 - abrasion resistance, 10-11, 24-4
 - absorption of stone, 10-11, 24-4
 - adhesive and panel installation, 10-5
 - anchorage, 10-6
 - anchors, 10-3
 - back-checking, 10-4
 - backs of pieces, 10-4
 - bolted connections, back-checking, 10-4
 - calcium carbonate and weather resistance, 10-13
 - caulking, 10-6
 - cleaning, 10-6
 - color, 10-7, 10-8
 - compressive strength, 10-10, 24-4
 - countertops, 17-2
 - cramps, 10-3
 - damaged stone, repairing, 10-2
 - defined, 23-25
 - density, 10-10, 24-4
 - dowels, 10-3
 - drips, 10-3 to 10-4
 - efflorescence, 10-12 to 10-13
 - expansion joints, 10-6
 - exterior panel installation, 10-5
 - finishes, 10-3, 10-9
 - fire resistance, 10-11
 - flexural strength, 10-10, 24-4
 - flexure testing, 4-7
 - flooring, 10-10
 - formation, 10-7
 - furniture and tops, 19-1
 - geological classification, 10-6 to 10-8, 21-70
 - hardness, 10-11
 - installation, 10-5 to 10-6
 - interior panel installation, 10-5
 - lippage, 10-3
 - modulus of rupture, 10-11, 24-4
 - moldings, 10-3 to 10-4
 - mortar, 10-3
 - mortar joints, 10-6
 - mortar setting of, 10-5
 - packing and loading, 10-4
 - panel thickness, 10-3
 - phyllite, 10-7 to 10-8
 - physical properties, 10-10 to 10-11, 24-4
 - plastic lime hydrate, 10-3
 - protection of, 10-6

- quality, 10-7
- safety factors, 10-12
- sampling, 10-9
- schist, 10-8
- sealant joints, 10-6
- sealants, 10-3
- seismic considerations, 10-12
- sizes, 10-9
- soundness, 10-10
- spandrel thickness, 10-3
- staining, 10-13
- storage, 10-4
- strength, 10-11
- texture, 10-8
- thermal conductivity, 10-11
- thickness, 10-9
- usage tips, 10-10
- veining, 10-8
- wall facing thickness, 10-3
- washes, 10-3 to 10-4
- water absorption, 4-3, 10-11 to 10-12, 24-4
- weather resistance, 10-12
- weep tubes, 10-6
- wind loads, 10-12
- sling, defined, 23-25
- slip joint, defined, 23-25
- slip resistance, 4-1, 4-9, 21-75
- slip sill
 - See also* lug sill
 - defined, 23-25
- slurry, defined, 23-25
- smooth finish
 - defined, 23-25
 - limestone, 6-10
 - travertine, 12-7, 12-10
- snapped edge. *See* guillotine (23-13)
- snow melting chemicals, 13-19
- soapstone
 - absorbency, 11-6
 - caulking, 11-4
 - chemical reactivity, 11-5
 - chlorite, 11-5
 - cleaning, 11-4
 - color, 11-6
 - countertops, 17-2
 - damaged stone, repairing, 11-2
 - defined, 23-25
 - dolomite, 11-5
 - drips, 11-3
 - electrical properties, 11-6
 - expansion joints, 11-3
 - finishes, 11-3
 - fire resistance, 11-6
 - geological classification, 11-4, 21-70
 - hardness, 11-5
 - heat retention, 11-5
 - installation, 11-3 to 11-4
 - magnesite, 11-5
 - micas, 11-5
 - mineralogy, 11-5
 - moldings, 11-3
 - packing and loading, 11-3
 - physical properties, 11-5 to 11-6
 - protection of, 11-4
 - sampling, 11-1 to 11-2
 - sealants, 11-4
 - steatite, 11-5
 - talc, 11-5
 - washes, 11-3
- soffit hanger, 14-D.24
- soffits
 - back anchors, 14-D.18
 - defined, 23-25
 - disc hangers, 14-D.18
 - expansion bolts, 14-D.18
 - flat strap hangers, 14-D.18
 - L-spline anchors, 14-D.18
 - stone, installation, 14-14, 14-15
- solid-state transformation, 1-1
- solvents, 21-84
- sound attenuation membranes, 13-7
- soundness
 - defined, 23-25
 - marble and onyx, 7-15 to 7-16
 - shower partitions, 16-5
 - showers, residential, 16-10
 - steam rooms and showers, 16-10
 - urinal partitions, 16-4
 - wet areas, 16-1
- source of supply
 - granite, 5-2
 - limestone, 6-1
 - marble, 7-1
 - onyx, 7-1
 - quartz-based stone, 8-1
 - serpentine, 9-1
 - slate, 10-1
 - soapstone, 11-1
 - travertine, 12-1
- spall, defined, 23-25
- spalls, 21-23, 21-26
- spandrel, 23-14, 23-22
 - defined, 23-25
- spandrel beam, 23-27
- spans
 - countertops, 17-4
 - furniture and tops, 19-1
- specific gravity, 4-1, 4-3
- specific gravitation language, sample, xvii to xviii
- splashes and stone tile countertops, 17-9
- splay, 23-27
 - defined, 23-25
- splines
 - countertops, 17-11
 - for toilet partitions, 16-D.1
- spline joint reinforcement at sink, 17-D.4
- split, defined, 23-25
- split face ashlar, 14-D.21
- split faced finish, 5-7
- split-faced stone, defined, 23-25
- split-tail anchor, exterior stone veneer, 14-D.2, 14-D.3
- split-tail straps, 14-D.23
- splitting of slabs, 8-11
- spot or spotting, defined, 23-25
- spreader bar, defined, 23-25
- spreading devices/tools, 21-43
- spring clip, 14-D.25
- spring clip with collar, 14-D.25
- springer, 23-14, 23-22
- square feet to square meters, 24-1
- square meters to square feet, 24-1
- squareness, tolerances, 22-5
- stacked bond, defined, 23-26
- stain prevention with travertine, 12-3 to 12-4
- staining
 - granite, 5-13 to 5-14
 - grout, 14-8
 - marble and onyx, 7-19, 7-20 to 7-21
 - quartz-based stone, 8-13 to 8-14
 - sealants, 13-19, 14-8 to 14-9
 - serpentine, 9-16
 - slate, 10-13
 - travertine, 12-14
- stains
 - accelerators, 21-40
 - biological stains, 21-81, 21-83
 - efflorescence, 21-22, 21-81 to 21-82
 - eradication of, 21-22
 - etch marks, 21-81
 - fire and smoke damage, 21-81
 - flammable materials, 21-83
 - food and beverage, 21-21
 - grout stains, 21-22
 - hazing, 21-22
 - identifying causes, 21-21 to 21-22
 - ink stains, 21-81, 21-83
 - inorganic metal stains, 21-81, 21-82
 - oil-based stains, 21-80 to 21-81, 21-82
 - organic stains, 21-81, 21-82

- paint stains, 21-81, 21-82 to 21-83
- poulticing, 21-82 to 21-83
- rust, 21-21
- soiling, 21-22
- subsurface water, 21-26
- water spots and rings, 21-81
- stair tread edge, *17-D.16, 19-D.3*
- stair treads
 - abrasive hardness, 14-13
 - color, 14-14
 - deflection of, 14-13
 - details, *13-D.6 to 13-D.8*
 - finishes, 14-13
 - granite, 14-13
 - hardness, 14-13
 - installation, *13-D.6 to 13-D.8, 14-13, 14-14*
 - limestone, 14-13
 - limitations, 14-13
 - marble, 14-13
 - setting, *13-D.6 to 13-D.8*
 - sizes, 13-17
 - slip resistance, 14-13
 - stainless steel dowels, *13-D.6 to 13-D.8*
 - thickness, 13-17
 - traffic after installation, 14-13
- stairs, 13-17
 - abrasion resistance, 13-4
- Standard 51 and stone, 2-4
- standard set method, window stools, 18-4
- standards, importance of, 2-1
- standards organizations, 2-1
- static coefficient of friction, 4-9
 - wet tests, 4-9
- steam rooms and showers
 - color, 16-10
 - color, 16-7
 - details, *16-D.8*
 - elevations, *16-D.6 to 16-D.7*
- stone slab
 - ceilings, 16-9
 - fabrication, 16-7
 - full mortar method, 16-9
 - grout, 16-9
 - installation, 16-9
 - moisture proofing, 16-8
 - polished finish, 16-7
 - sealing, 16-8
 - sizes, 16-7
 - soundness, 16-7
 - steam, effects of, 16-9
 - stone ceiling, 16-7
 - thin-set method, 16-9
 - ceilings, 16-12
- stone tile
 - exposed edges, 16-10
 - fabrication, 16-10
 - full mortar method, 16-11
 - grout, 16-12
 - installation, 16-11 to 16-12
 - marble groups, 16-10
 - moisture proofing, 16-12
 - polished finish, 16-10
 - sizes, 16-10
 - soundness, 16-10
 - steam, effects of, 16-11 to 16-12
 - thickness, 16-10
 - thin-set method, 16-11
- steam, effects of, 16-9, 16-11 to 16-12
- steel pan, for stair treads, *13-D.6, 13-D.8*
- steel stringers, for stair treads, *13-D.8*
- sticking, 7-15 n11, 21-8
 - defined, 23-26
- stiles for toilet partitions, 16-3, *16-D.1 to 16-D.2*
- stone
 - defined, 23-26
 - product of nature, 3-1
 - rock vs., 1-1
 - size of and cost, 3-7
 - stains, 21-26
 - thickness, 3-7
 - weight, 13-5
- stone base, installation, 14-15
- stone behavioral groups
 - additional resources, 21-121
 - defined, 21-11
- stone formation, 21-1 to 21-2
- stone in green building, ix to x
- stone paving and underlayment
 - limitations, 13-5
- stone samples, 3-6
- stone slab layout countertops, 17-3
- stone tile countertops, 17-2
 - installation, 17-9
- stone types
 - identification, 21-17
 - location, 21-17
 - mixing, 3-3
- stone units, preparation, 13-18
- stool, 23-24
 - defined, 23-26
- straight edge, *17-D.16, 19-D.3*
- straps, "L", *14-D.23*
- straps, "Z", *14-D.23*
- straps, cramp, *14-D.23*
- straps, dovetail, *14-D.23*
- straps, split-tail, *14-D.23*
- straps, twisted, *14-D.23*
- straps, two way, *14-D.23*
- stratification, defined, 23-26
- strength, 4-1
 - exterior application, 3-3
 - limestone, 6-12 to 6-13
 - marble and onyx, 7-17
 - quartz-based stone, 8-12
 - serpentine, 9-14
 - slate, 10-11
 - travertine, 12-13
 - uniformity, 4-3
 - units of measure, 4-5
- strength testing, 4-5 to 4-9
- string course, defined, 23-26
- stringers, steel, for stair treads, *13-D.8*
- stripping, defined, 23-26
- structural contraction and exterior applications, 3-3 to 3-4
- structural distortion and exterior applications, 3-4
- structural flaws and resin-impregnated slabs, 17-11
- structural support, consultants, 21-26
- stud walls, 14-14 to 14-15
- stun marks, 21-13
- stylolites, 7-9 to 7-10
 - defined, 23-26
- subcontractor responsibilities, 17-3
- subduction, 1-3
- subflooring
 - concrete, 13-14 to 13-15
 - frame construction, 13-5
 - plywood, 13-11, 13-15 to 13-16, 14-10
 - wood, 13-15
- sub-slab, *13-D.1*
- substrate
 - high moisture, 21-26
 - maintenance, 21-76
 - tolerances, 22-8
- subtops, 17-3, *17-D.8*
 - outdoor kitchens, 17-13
 - stone tile countertops, 17-9
- supply source
 - granite, 5-2
 - limestone, 6-1
 - marble, 7-1
 - onyx, 7-1
 - quartz-based stone, 8-1
 - serpentine, 9-1
 - slate, 10-1
 - soapstone, 11-1
 - travertine, 12-1
- support, defined, 23-26
- support anchorage for exterior stone veneer, *14-D.7*

support documentation, samples, 3-7
support systems, pedestal supported, 13-13
surface plane, tolerances, 22-8
surface protection for countertops, 17-12 to 17-13
surface sealers, 13-7 to 13-9
vertical surfaces, 14-10
surface treatments, 21-6 to 21-7
surround for fireplace facings, *14-D.20*
sustainability, vii to ix, x

T

T, stainless steel or extruded aluminum, *14-D.1, 14-D.2, 14-D.3*
T-31 back anchor, *14-D.23, 14-D.24*
talc, 9-10, 11-5
hardness, 21-2
tannin-containing woods
limestone, 6-5
travertine, 12-5
TCNA (Tile Council of North America), 13-14
defined, 23-26
Handbook for Ceramic, Glass, and Stone Tile Installation, 21-18, 21-19
Technical Bulletins, "Dimension Stone Anchorage; Theory, Practice, & Components", 21-18
temperate climate and limestone exteriors, 3-4
template, defined, 23-26
tensile strength
precast concrete panels, 20-1
stone veneer panels, 20-1
terrazzo
defined, 23-26
plugs, 21-30
testing
knowing when required, 2-2
when not available, 2-2
testing mockups
precast concrete panels, 20-1
stone veneer panels, 20-1
texture
defined, 23-26
granite, 5-10
limestone, 6-10
marble and onyx, 7-13
quartz-based stone, 8-9 to 8-10
serpentine, 9-12
slate, 10-9

travertine, 12-10
textured finish, defined, 23-26
thermal (flamed) finish, defined, 21-6
thermal conductivity of marble and onyx, 7-17
thermal expansion
exterior applications, 3-4
marble and onyx, 7-20, 7-21
quartz-based stone, 8-14
thermal finish, 3-2
defined, 23-26
granite, 5-7
limestone, 6-10
weakening of stone, 6-10, 8-10
thermal insulation, 14-10
thick beam behavior, 5-12
thick bed, coursed ashlar, installation, 14-13
thickness
countertops, 17-4
cubic sills, 18-3
exterior pavers, 14-2, 14-5
flooring, 14-5
furniture and tops, 19-1
granite, 5-7, 5-10
interior flooring, 14-3
limestone, 6-11
marble and onyx, 7-14
measuring, 21-18
overhangs, 19-1
pavers, 14-2 to 14-3
precast concrete panels, 20-1
quartz-based stone, 8-10
serpentine, 9-12
showers, residential, 16-10
slate, 10-9
stair treads, 13-17
steam rooms and showers, 16-10
stone veneer panels, 20-1
thresholds, 14-11
tolerances, 22-5
translucence, 7-21
travertine, 12-10
water absorption, 4-3
window stools, 18-3
thin bed mortar, 14-9
thin sections, 4-1
thin stone, defined, 23-26
thin veneer, *14-D.21*
thin-bed mortar, 13-16
thin-set method
steam rooms, 16-9, 16-11
steam showers, 16-9, 16-11
window stools, 18-4
thin-set mortar, 13-8 to 13-9, 14-6 to 14-7

thin-stone pavers
stair treads, 14-13
structural qualities, 4-3
water absorption, 4-3
three-sided adhesion, 13-10, 14-9
thresholds, 13-17
abrasive hardness, 14-11
color, 14-11
damage prevention, 21-25
defined, 23-26
exposed edges, 14-11
fabrication, 14-11
finishes, 14-11
full mortar method, *13-D.5*
granite, 14-11
hardness, 14-11
installation, 14-11, 14-12
limestone, 14-11
marble, 14-11
sizes, 14-11
stone abutment in floors, 14-7, 14-11
thickness, 14-11
thin-set method, *13-D.5*
traffic after installation, 14-11
varying bed depth mortar method, *13-D.5*
white portland cement, 14-11
tiebacks, wire, *14-D.25*
tiger's eye, 9-10
tile
defined, 14-1, 23-27
installation, 14-15
mixing, 3-3
modular, 3-3
selection, 13-1
thickness, 13-2
Tile Council of North America (TCNA), 13-14
defined, 23-26
Handbook for Ceramic, Glass, and Stone Tile Installation, 21-18, 21-19
tile reinforcement for stone tile countertops, 17-9
tile width for stone tile countertops, 17-9
tilt shop cart, defined, 23-27
tin oxide, defined, 23-27
toilet and shower compartments
ceiling-hung, 7-6, 9-7
corrosion-resistant angles, 7-6, 9-7
dowel fastenings, 7-6, 9-7
marble and onyx, 7-6
serpentine, 9-7
toilet partitions
ceiling channel, 16-3

- ceiling-hung, *16-D.1*
 - color, 16-1
 - fabrication, 16-3
 - finishes, 16-3
 - floor-mounted, *16-D.1*
 - installation, 16-3
 - sizes, 16-3
 - splines, *16-D.1*
 - stiles, 16-3, *16-D.1* to *16-D.2*
 - tolerances
 - alignment, 22-7 to 22-8
 - anchors, 22-6
 - applicability, 22-3
 - asymmetrical bilateral
 - tolerances, 22-1 to 22-2
 - bilateral tolerances, 22-1 to 22-2
 - bullnose edge, *22-D-App B*
 - chamfer edge, *22-D-App B*
 - defined, 22-1
 - edges, 22-6
 - fabrication, 22-5 to 22-6
 - face size, 22-5, *22-D-App B*
 - flatness, 22-6
 - formatting differences, 22-2
 - installation, 22-7 to 22-8
 - joint width, 21-20, 22-7
 - limit tolerances, 22-2
 - lippage, 21-20, 22-7
 - percentage tolerances, 22-2
 - quartz-based stone, 8-10
 - quirk miter, *22-D-App B*
 - squareness, 22-5
 - substrate, 22-8
 - surface plane, 22-8
 - symmetrical bilateral
 - tolerances, 22-1
 - thickness, 22-5
 - tiles, 14-1
 - unilateral tolerances, 22-2
 - tooled finish, 7-14
 - defined, 23-27
 - topaz, hardness, 21-2
 - topical sealers, 21-23
 - traffic after installation, exterior pavers, 14-5
 - transition strips, 13-11, 13-18
 - damage prevention, 21-25
 - translucence, 3-1
 - color, 7-21
 - crystal structure, 7-21
 - defined, 23-27
 - marble and onyx, 7-20, 7-21
 - surface finish, 7-21
 - thickness, 7-21
 - transverse strength. *See* flexural strength
 - travertine
 - See also* MTL
 - (marble/travertine/limestone)
 - abrasion resistance, 24-4
 - absorption of stone, 24-4
 - adjacent to water, 12-4
 - anchorage, 12-6
 - anchors, 12-3
 - as type of limestone, 12-8
 - back-checking, 12-4
 - backs of pieces, 12-4
 - bolted connections, back-checking, 12-4
 - carving, 12-5
 - caulking, 12-7
 - clay balls, 12-9
 - cleaning, 12-7
 - cold weather and installation, 12-6
 - color, 12-10
 - composition of, 1-6, 12-8 to 12-9
 - compressive strength, 24-4
 - countertops, 17-2
 - cross cut stones, 12-11
 - damaged stone, repairing, 12-2
 - dampproofing, 12-14
 - defined, 21-12 to 21-13, 23-27
 - deicing chemicals, 12-13
 - density, 24-4
 - distinguished from onyx, 7-13
 - drips, 12-4
 - effective techniques, 21-13
 - efflorescence, 12-14
 - expansion joints, 12-6 to 12-7
 - filling, 12-11
 - finishes, 12-7, 12-10
 - fleuri cut, 3-2, 12-11, 24-4
 - flexural strength, 24-4
 - furniture and tops, 19-1
 - geological classification, 12-8 to 12-10, 21-70
 - hardness, 12-13, 21-2
 - horizontal applications, 12-6
 - hydrated lime, 12-3
 - installation, 12-5 to 12-7
 - modulus of rupture, 24-4
 - moldings, 12-4
 - mortar joints, 12-6
 - packing and loading, 12-5
 - panel thickness, 12-4
 - paving stone, 12-6
 - physical properties, 12-12, 24-4
 - plastic setting pads, 12-6
 - pointing mortar, 12-3
 - portland cement, 12-5
 - protection of, 12-7
 - reflection, 13-19
 - sampling, 12-10 to 12-11
 - sand, 12-3
 - scaling, 12-14
 - sealant joints, 12-6
 - sealants, 12-3
 - setting mortar, 12-3
 - sizes, 12-10
 - stain prevention, 12-3 to 12-4
 - staining, 12-14
 - storage, 12-5
 - stun marks, 21-13
 - texture, 12-10
 - thickness, 12-10
 - tufa, 12-9
 - tuff, 12-9
 - usage tips, 12-11
 - vein cut, 12-11
 - veining, 12-10
 - vertical surfaces, 12-6
 - voids, 13-19
 - washes, 12-4
 - water absorption, 24-4
 - water and installation, 12-5
 - weep tubes, 12-7
 - white masonry cement, 12-3
 - white portland cement, 12-3
 - tread, 23-25
 - defined, 23-27
 - trim, defined, 23-27
 - triple waterfall edge, *17-D.16, 19-D.3*
 - troubleshooting, vertical surfaces, 14-16 to 14-17
 - tufa, 12-9
 - tuff, 12-9
 - tumbled finish, 3-2
 - defined, 23-27
 - limestone, 6-10
 - MTL, 21-58
 - slate, 10-9
 - travertine, 12-7
 - twisted straps, *14-D.23*
 - two-way straps, *14-D.23*
 - tympanum, 23-18
- ## U
- U clamp bars, *14-D.25*
 - U cramp straps, *14-D.23*
 - ultimate capacity, defined, 23-27
 - uncoupling membranes, 13-7, 14-3
 - undercut back anchors, *14-D.24*
 - undercut, defined, 23-27
 - underlayment, self-leveling, 13-5
 - undermount sink support, *17-D.8*
 - unfilled finish, 12-10
 - uniformity, 4-3
 - uniformity of material, relative value of, 3-1

unit, defined, 23-27
United States Green Build Council (USGBC), vii to viii
units of measure for strength, 4-5
upward crack, repairs, 21-43, 21-44
urethane
 adhesives and patching
 materials, 21-41
 properties, 21-49
urinal partitions
 color, 16-4
 details, 16-D.3
 fabrication, 16-4
 finishes, 16-4
 installation, 16-4
 sizes, 16-4
 soundness, 16-4
urinal screens, 16-D.3
 defined, 23-27
USGBC (United States Green Build Council), vii to viii
utilities
 power source, 21-25
 water discharge and disposal, 21-25
 water supply, 21-25
UV light exposure
 resin-impregnated slabs, 17-11
 outdoor kitchens, 17-13

V

vacuum cups, defined, 23-27
vacuum lifter, defined, 23-27
vanities, 17-D.11
variegated materials, 3-1
variegated MTL group
 defined, 21-14
 effective techniques, 21-14
vein, defined, 23-27
vein cut, 23-3, 23-11
 defined, 23-27
 marble and onyx, 7-16
 serpentine, 9-13
 travertine, 12-11
 veneer cutting, 7-D.1
vein trend in stone tile countertops, 17-9
veined materials, 3-1
vener, defined, 23-27
vener cutting
 fleuri cut, 7-D.1
 granite, 5-10
 limestone, 6-11
 marble and onyx, 7-D.1
 serpentine, 9-13
 vein cut, 7-D.1
vener patterns
 blend pattern, 7-D.2

 book match pattern, 7-D.3
 diamond match pattern, 7-D.3
 end match pattern, 7-D.3
 end slip pattern, 7-D.2
 marble and onyx, 7-D.2 to 7-D.3
 quarter match pattern, 7-D.3
 side slip pattern, 7-D.2
vener, adhered, installation, 14-13 to 14-14
vener, dry stack, 14-D.22
vener, independently supported, installation, 14-11 to 14-12
vener, stacked
 installation, 14-12
 shims, 14-10
vener, stone-faced, 20-D.1 to 20-D.2
 coefficient of thermal expansion, 20-1
 color, 20-1
 compressive strength, 20-1
 finishes, 20-1
 limitations, 20-1
 modulus of elasticity, 20-1
 physical properties, 20-1
 shear strength, 20-1
 sizes, 20-1
 tensile strength, 20-1
 testing mockups, 20-1
 thickness, 20-1
 installation, 20-2
vener, thin, 14-D.21
vertical surfaces
 anchors and accessories, 14-D.23 to 14-D.25
 exterior stone veneer, 14-11 to 14-14
 interior, 3-5
 shop drawings, 14-1 to 14-2
vitrification
 See crystallization
 defined, 21-64
VOCs (volatile organic compounds), 21-40
 sealers, 21-68
voids, 21-23
 maintenance, 21-76
 travertine, 13-19
volatile organic compounds (VOCs), 21-40
 sealers, 21-68
volcanic rock, cleaning and maintenance, 21-78
volume
 conversion ratios, 24-2
 measurement, 4-4 to 4-5
vug, defined, 23-27 to 23-28

W

wainscot, defined, 23-28
wall tie, defined, 23-28
wall tile
 adhesive
 marble and onyx, 7-6
 serpentine, 9-7
 marble and onyx, 7-6
 serpentine, 9-7
walls
 bearing, defined, 23-28
 cavity, defined, 23-28
 damage prevention, 21-25
 durability of installation, 3-4
 warranty provision, suggested, xii
wash, 23-7
 defined, 23-28
washes
 granite, 5-4
 limestone, 6-4
 marble and onyx, 7-4
 quartz-based stone, 8-3
 serpentine, 9-4
 slate, 10-3 to 10-4
 soapstone, 11-3
 travertine, 12-4
wastage, 3-3
 related to cost, 3-7
waste management, viii to ix
water absorption, 4-4
water and serpentine installation, 9-6
water control slopes, 21-20
water damage, 21-24
water discharge, commercial and historical restoration, 21-86
water jet, defined, 23-28
water misting, 21-84
water recycling system, defined, 23-28
water repellent, defined, 23-28
water resistance
 interior application, 3-5
 limestone, 6-4
water stop, spline type, 14-D.9
water supply, commercial and historical restoration, 21-85 to 21-86
water table, defined, 23-28
water vapor, 3-4
water vapor permeability of marble and onyx, 7-17
water-jet finish, defined, 23-28
water-jet flamed finish, 3-2
waterfall edge, 17-D.16, 19-D.3
waterproof membranes, 14-4
waterproof pan receptor types, 16-D.4

waterproofing
 showers, residential, *16-D.8, 16-D.10*
 steam rooms, *16-12, 16-D.8*
 steam showers, *16-12, 16-D.8*

waxing, *7-15 n12*
 defined, *23-28*

wear, defined, *23-28*

wear resistance, *4-1*

weathering, *21-24*
 chemical, *1-1 to 1-2*
 defined, *23-28*

websites, organizations, *iv*
 green references, *xi*

wedging, defined, *23-28*

weep holes
 defined, *23-28*
 granite, *5-6*
 limestone, *6-7*
 marble and onyx, *7-7*
 placement, *15-3*
 quartz-based stone, *8-6*
 serpentine, *9-8*
 showers, steam rooms, and steam showers, *16-9, 16-12*
 slate, *10-6*
 travertine, *12-7*
 weep holes, showers, *16-7*

weight
 conversion ratios, *24-2*
 mortar bed, *13-5*
 stone, *13-5*

well-rounded grain (sand), *1-5*

wet areas, *13-18, 14-16*
 anchors, *16-1*
 definitions, *16-2*
 diagnostic considerations, *21-24*
 evaluation of, *21-20 to 21-21*
 interior cladding, *14-16*
 oil-based putty, *16-1*
 plumbing sealants, *16-1*
 soundness, *16-1*
 white portland cement, *16-1*

wet/dry testing, *4-4*

wet/dry vacuums, *21-37*

wet set, defined, *16-2*

wet weight and specific gravity, *4-4 to 4-5*

White House, greening of, *vi to vii*

white portland cement
 cubic sills, *18-3*
 exterior cubic stone coping and walls, *18-1*
 granite, *14-11, 14-13, 18-1, 18-3*
 light colored stones, *13-18*
 limestone, *14-13, 16-1, 18-1, 18-3*
 marble, *14-11, 14-13, 18-1, 18-3*
 stair treads, *14-13*
 thresholds, *14-11*
 wet areas, *16-1*
 window stools, *18-3*

windload and exterior applications, *3-3*

window stools
 bonding, *18-3*
 color, *18-3*
 corrosion-resistant metals, *18-3*
 details, *18-D.2*
 fabrication, *18-3*
 finishes, *18-3*
 frame construction, *18-D.2*
 installation, *18-4*
 masonry construction, *18-D.2*
 oil-based putty, *18-3, 18-4*
 sealants, *18-3, 18-4*
 sizes, *18-3*
 standard set method, *18-4*
 thickness, *18-3*
 thin-set method, *18-4*

wire "goose neck" anchor, *14-D.25*

wire lace anchor, *14-D.25*

wire loop anchor, *14-D.21*

wire sawing, defined, *23-28*

wire tieback, *14-D.25*

wood
 chemically treated, *6-5, 12-5*
 skids, *6-5, 12-5*
 tannin-containing, *6-5, 12-5*

wood studs, *14-15*

wood subfloor
 heated floor systems, *13-D.4, 14-10*
 mortar bed, *13-D.3*

work, considerable, *i to 25-28*

work platforms, commercial and historical restoration, *21-85*

wythe, defined, *23-28*

X

X-ray diffraction (XRD), *4-1*

Y

Young's modulus. *See* modulus of elasticity

Z

Z bar, *14-D.25*

Z straps, *14-D.23*